

Product data sheet

Specifications



Rack PDU, Basic, 1U, 30A, 208V, (10) C13



AP9571A

Overview

Presentation	Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (10) C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
Lead time	Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	12 ft (3.7 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets User Manual

Complementary

Input Voltage	200 V 208 V 230 V
Height	1.73 in (4.4 cm)
Width	17.52 in (44.5 cm)
Output Voltage	208 V
Depth	3.03 in (7.7 cm)
Product Weight	5.62 lb(US) (2.55 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Input Plug Type	NEMA L6-30P
Mounting Mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Line Rated Current	24 A
Acceptable Input Voltage	200...240 V
Max line current	30 A

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz
Outlet type and quantity	10 IEC 60320 C13

Environment

Product Certifications	cUL Listed PSE UL Listed
Standards	UL 60950
Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304272755
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.73 in (17.1 cm)
Package 1 Width	6.85 in (17.4 cm)
Package 1 Length	19.02 in (48.3 cm)
Package 1 Weight	8.02 lb(US) (3.64 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 65

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

Image of product / Alternate images

Alternative

