

Product data sheet

Specifications



Rack PDU Extender, Basic, 2U, 30A, 100/120/200/208V, (4)L5-30



AP7583

Overview

Lead time Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	28 ft (8.5 m)
Provided Equipment	Installation guide Rack Mounting brackets

Complementary

Input Voltage	120 V 208 V
Height	3.50 in (8.9 cm)
Width	17.20 in (43.7 cm)
Output Voltage	120 V
Depth	3.50 in (8.9 cm)
Product Weight	14.02 lb(US) (6.36 kg)
Mounting Location	Front Rear
Mounting preference	Lower
Input Plug Type	NEMA L14-30P
Mounting Mode	Not rack-mountable
Rack units	2U
Mounting position	Horizontal
Line Rated Current	24 A
Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz
Outlet type and quantity	4 NEMA L5-30R

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Product Certifications	cUL Listed METI Denan UL Listed
Standards	CSA C22.2 No. 107.1 UL 1778
Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304222576
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.98 in (15.2 cm)
Package 1 Width	20.51 in (52.1 cm)
Package 1 Length	20.51 in (52.1 cm)
Package 1 Weight	16.03 lb(US) (7.27 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

Halogen content performance

Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Use Again

Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Take-back

Yes