

Product data sheet

Specifications



Rack PDU, Metered, 1U, 15A, 100/120V, (8) 5-15



AP7800B

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

| | |
|----------------------------------|--|
| Product or Component Type | PDU |
| PDU Type | Metered |
| Cord length | 12 ft (3.7 m) |
| Number of cables | 1 |
| Provided Equipment | Cord retention bracket(s) Installation guide Rack Mounting brackets User Manual |

Complementary

| | |
|---------------------------------|-----------------------|
| Input Voltage | 100 V 120 V |
| Height | 1.73 in (4.4 cm) |
| Width | 17.48 in (44.4 cm) |
| Output Voltage | 120 V |
| Depth | 4.02 in (10.2 cm) |
| Product Weight | 3.81 lb(US) (1.73 kg) |
| Mounting Location | Front Rear |
| Mounting preference | No preference |
| Input Plug Type | NEMA 5-15P |
| Mounting Mode | Rack-mounted |
| Rack units | 1U |
| Mounting position | Horizontal |
| Line Rated Current | 12 A |
| Input current limits | 15 A |
| Load Capacity | 1440 VA |
| Input Frequency | 50/60 Hz |
| Outlet type and quantity | 8 NEMA 5-15R |

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|--|--|
| Product Certifications | cUL Listed CSA METI Denan UL Listed VCCI |
| Standards | FCC Part 15 class A ICES-003 UL 60950 |
| Ambient air temperature for operation | 23...113 °F (-5...45 °C) |
| Relative Humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|--------------------------|---------------------------|
| Category | 11309-APC RESALE PRODUCTS |
| Discount Schedule | APC1 |
| GTIN | 731304331452 |
| Returnability | No |
| Country of origin | PH |

Packing Units

| | |
|-------------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.52 in (6.4 cm) |
| Package 1 Width | 13.27 in (33.7 cm) |
| Package 1 Length | 18.50 in (47 cm) |
| Package 1 Weight | 6.42 lb(US) (2.91 kg) |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 2 years repair or replace |
|-----------------|---------------------------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 3302

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery Yes

Take-back Yes

Image of product / Alternate images

Alternative



