

# Product data sheet

Specifications



## APC 17" Rack LCD Console

AP5717

### Overview

<b>Presentation</b>	1U rack-mountable keyboard, mouse, and LCD console with US English keyboard layout.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	100 V 240 V
<b>Number of rack unit</b>	1U
<b>Provided equipment</b>	C13-C14 power cord Documentation CD Firmware upgrade cable Installation guide NEMA 5-15 power cord PS2 KVM cable Single user rack mount kit USB cable USB KVM cable

### Physical

<b>Color</b>	Black
<b>Height</b>	1.73 in (4.4 cm)
<b>Width</b>	18.98 in (48.2 cm)
<b>Depth</b>	24.17 in (61.4 cm)
<b>Product Weight</b>	35.05 lb(US) (15.9 kg)
<b>Mounting Location</b>	Front Rear
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Rack-mounted
<b>Maximum Mounting Depth</b>	41.33 in (104.98 cm)
<b>minimum mounting depth</b>	26.77 in (68 cm)

### Input

<b>Input Frequency</b>	50/60 Hz
------------------------	----------

### Conformance

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Product Certifications</b>	C-tick CE Industry Canada KCC NOM UL Listed VDE TAA compliance
-------------------------------	---

---

<b>Standards</b>	EN 55022 Class A EN 55024 EN 60950 FCC Part 15 class A IEC 60950
------------------	--

---

## Environmental

---

<b>Ambient air temperature for operation</b>	32...104 °F (0...40 °C)
--	-------------------------

## Supported Hardware

---

<b>Display colour</b>	16 colours
-----------------------	------------

---

<b>Display size</b>	17 inch
---------------------	---------

---

<b>Trackball Type</b>	PS/2 Touchpad USB mouse
-----------------------	----------------------------

---

<b>Display Type</b>	LCD display
---------------------	-------------

---

<b>LCD Power Consumption</b>	19 W
------------------------------	------

---

<b>Pixel size</b>	0.26
-------------------	------

---

## Ordering and shipping details

---

<b>GTIN</b>	731304283232
-------------	--------------

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	5.98 in (15.2 cm)
-------------------------	-------------------

---

<b>Package 1 Width</b>	32.52 in (82.6 cm)
------------------------	--------------------

---

<b>Package 1 Length</b>	26.50 in (67.3 cm)
-------------------------	--------------------

---

<b>Package 1 Weight</b>	42.90 lb(US) (19.46 kg)
-------------------------	-------------------------

---

## Contractual warranty

---

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	59
--	----

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
-----------------------------------	---------------------------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

Halogen content performance	Product contains halogen above thresholds
-----------------------------	---

### Use Again

#### Repack and remanufacture

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

Take-back	Yes
-----------	-----

WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
------	--

Image of product / Alternate images

Alternative

---



