

Product data sheet

Specifications



RACK PDU, BASIC, HALF HEIGHT, 100-240V/20A, 220-240V/16A, (14) C13

AP6003A

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Basic

Provided Equipment Installation guide
Safety guide

Complementary

Input Voltage 230 V

Height 20.59 in (52.3 cm)

Width 2.20 in (5.6 cm)

Output Voltage 100 V
120 V
200 V
208 V
230 V
240 V

Depth 1.85 in (4.7 cm)

Product Weight 4.14 lb(US) (1.88 kg)

Mounting Location Side

Mounting preference Lower

Input Plug Type IEC 60320 C20

Mounting Mode Not rack-mountable

Rack units 0U

USB compatible No

Mounting position Vertical

Line Rated Current 16 A

Acceptable Input Voltage 100...240 V

Max line current 20 A

Input current limits 20 A

Load Capacity 3300 VA

Input Frequency 50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Outlet type and quantity	14 IEC 60320 C13
--------------------------	------------------

Environment

Product Certifications	cUL Listed UL Listed
------------------------	-------------------------

Ambient air temperature for operation	32...122 °F (0...50 °C)
---------------------------------------	-------------------------

Relative Humidity	5...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
-------------------------------------	--------------------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--------------------------------------------------

Ordering and shipping details

GTIN	731304327769
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	24.09 in (61.2 cm)
------------------	--------------------

Package 1 Width	4.21 in (10.7 cm)
-----------------	-------------------

Package 1 Length	4.84 in (12.3 cm)
------------------	-------------------

Package 1 Weight	5.62 lb(US) (2.55 kg)
------------------	-----------------------

SCC14	10731304327766
-------	----------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **48**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

SCIP Number **1cdb2fed-a06f-4574-913d-8df8e70936b2**

REACH Regulation [REACH Declaration](#)

Halogen content performance **Product contains halogen above thresholds**

Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **Yes**

Image of product / Alternate images

Alternative

