

Product data sheet

Specifications

APC IT Power Distribution Module 3 Pole 5 Wire 20A L21-20 200cm



PDM3520L2120-200

Overview

Presentation Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

Lead time Usually Ships within 3 Weeks

Main

Main Input Voltage 208 V 3 phase

Main Output Voltage 120 V

Provided Equipment Installation guide

Physical

Color Black

Height 5.0000000000 in (12.7 cm)

Width 17.5 in (44.5 cm)

Depth 16.0 in (40.6 cm)

Net Weight 3.51 lb(US) (1.59 kg)

Input

Input Frequency 60 Hz

Permissible voltage 200...240 V

Max line current 20 A

Output

Maximum Total Current Draw per Phase 20 A

Number of power socket outlets 1 NEMA L21-20

Conformance

Product Certifications UL Listed

Ordering and shipping details

GTIN 731304265177

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	5.0000000000 in (12.7 cm)
Package 1 Width	16.0 in (40.6 cm)
Package 1 Length	17.5 in (44.5 cm)
Package 1 Weight	5.5 lb(US) (2.5 kg)

Contractual warranty

Warranty	1 year repair or replace
-----------------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Take-back Transparency

Resource performance

✔ Take-Back Program Available

Well-being performance

✔ Mercury Free

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Under investigation

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)
