



Hi-Speed USB 2.0 SVGA Converter

Supports up to 6 additional displays, Silver/Blue

Part No.: **179225**

EAN-13: 0766623179225 | UPC: 766623179225

Easily connect another monitor, an LCD projector or another SVGA device to notebook or desktop computers.

The Manhattan Hi-Speed USB 2.0 SVGA Converter helps increase productivity, improve "desktop" arrangements and extend the visual work area across dual monitors. It helps make word processing, editing and multitasking more effective with less-overlapped windows, fewer hidden palettes and better-organized views. Users can read e-mail on one monitor and open attachments on the other. Large, complicated spreadsheets can be expanded and viewed without scrolling. Presentations are made more compelling with another monitor for more impact or viewing speaker notes on a separate display. The MANHATTAN Hi-Speed USB 2.0 SVGA Converter supports resolutions of up to 1600 x 1200 in 16-bit or 32-bit color, and its 16 MB DDRAM memory easily enhances the workspace without complicated installations or expensive equipment.

Easy to Install

The convenient Hi-Speed USB 2.0 connection eliminates the need to install another graphics card or struggle with compatibility issues. It's an ideal portable solution for notebook computers and desktop systems with graphics cards that lack additional outputs. It's easily installed without an external power supply on any Windows computer.

Features:

- Easily adds a monitor to a computer to expand visual areas

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Software manages up to six converters; easily add up to six displays to a single PC
- Ideal for notebook computers and graphics cards without additional outputs
- Primary, extended and mirror functions provide display continuity and multiple views
- Supports resolutions up to 1600 x 1200 in 16-bit or 32-bit color
- Portable and connects to any USB port without conflicts or external power supplies
- Windows compatible
- Three-Year Warranty

Specifications:

Standards and Certifications

- Hi-Speed USB 2.0
- EHCI
- CE
- FCC

General

- Chipset: MCT Trigger 1+
- Display memory: 16 MB DDRAM
- Bus-powered
- Connections: USB type-A male; HD 15 female
- Supports Suspend and Wake modes
- Driver supports up to 6 additional devices
- Rotation modes: 0°, 90°, 180°, 270°

Supported resolutions

- Widescreen:
 - 16:10; 1680 x 1050; 16/32 bits
 - 16:10; 1440 x 900; 16/32 bits
 - 16:10; 1280 x 800; 16/32 bits
 - 16:9; 1360 x 768; 16/32 bits
 - 16:9; 1280 x 720; 16/32 bits
 - 15:9; 1280 x 768; 16/32 bits
- Standard monitor:
 - 5:4; 1280 x 1024; 16/32 bits
 - 4:3; 1600 x 1200; 16/32 bits
 - 4:3; 1400 x 1050; 16/32 bits
 - 4:3; 1280 x 960; 16/32 bits
 - 4:3; 1152 x 864; 16/32 bits
 - 4:3; 1024 x 768; 16/32 bits
 - 4:3; 800 x 600; 16/32 bits

Physical

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Case material: ABS
- Dimensions: 8 x 4 x 2 cm (3.25 x 1.5 x 0.75 in.)
- Cable: 50 cm (19 in.)
- Weight: 79 g (2.8 oz.)

System Requirements

- Compatible with Windows 2000/XP/Vista/7/8/10
- Available Hi-Speed USB 2.0 ports

Package Contents

- Hi-Speed USB 2.0 SVGA Converter
- Instructions and driver CD



