

Product data sheet

Specifications



APC NetShelter Rack PDU Advanced, Metered, 3Phase, 11kW 400V 16A or 11.5kW 415V 20A, 42 Outlets, IEC309

APDU10250ME

! To be discontinued

! To be discontinued on: Sep 3, 2025

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Metered

Cord length 5.9 ft (1.8 m)

Complementary

Input Voltage 415 V 3 phase
400 V 3 phase

Height 58.66 in (149.0 cm)

Width 2.20 in (5.6 cm)

Output Voltage 240 V

Depth 2.17 in (5.5 cm)

Product Weight 12.6 lb(US) (5.7 kg)

Mounting Location Side

Mounting preference No preference

Input Plug Type IEC 60309 20 A 3P+N+PE

Mounting Mode Rack-mounted

Rack units 0U

Mounting position Vertical

Communication Port Protocol 1000BASE-T
10/100BASE-T

Line Rated Current 16 A

Acceptable Input Voltage 200...240 V
346...415 V

Input current limits 20 A

Load Capacity 11500 VA

Input Frequency 50/60 Hz

Outlet type and quantity 21 C13/C15/C19/C21
21C13/C15

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

| | |
|--|---|
| Product Certifications | UKCA TAA compliance BAA compliance |
| Standards | UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1 |
| IP Degree of Protection | IP44 |
| Ambient air temperature for operation | 23...140 °F (-5...60 °C) |
| Relative Humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|--------------------------|--------------|
| GTIN | 731304439684 |
| Country of origin | US |

Packing Units

| | |
|-------------------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 67.72 in (172 cm) |
| Package 1 Width | 4.57 in (11.6 cm) |
| Package 1 Length | 8.19 in (20.8 cm) |
| Package 1 Weight | 17.0 lb(US) (7.7 kg) |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 3 years repair or replace |
|-----------------|---------------------------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **8717**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **No**

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

4-in-1 outlet for increased flexibility



Acts as any of these outlet types:



C13



C15



C19



C21

Multiple color options available











