Specifications

Eaton EMI319-10



Catalog Number: EMI319-10

Eaton Metered Input rack PDU, 0U, 309-532P6W input, 17.3 kW max, 240/415V, 24A, 10 ft cord, Three-phase, Outlets: (24) C13, (6) C19

General specifications

Product Name	**Catalog Number**
Eaton metered input PDU	EMI319-10
UPC	**Product Length/Depth**
786685907208	66.5 in
Product Height	**Product Width**
2.09 in	2.05 in
Product Weight	**Warranty**
13.2 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Powering Business Worldwide

Product specifications

Form factor
0U (Vertical)

Outlet control
No

Phase
Three-phase

Wattage
17.3 kW max

Amperage Rating
24A

Input voltage
240/415V

Input connection
2 x Hardwired

Outlets
(24) C13, (6) C19

Cord length
10 ft

Frequency rating
50-60 Hz

Ethernet interface
Yes

Serial interface
RS-232

Operating Temperature
0° to 60°C (32° to 140°F)

Resources

Certification reports
Eaton RoHS Declaration of Conformity: ePDU G3

Drawings
Eaton ePDU G3 Metered Input EMI319-10 technical drawing

Eaton PDU EMI319-10 technical drawing

Manuals and user guides
Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 operations manual

Eaton ePDU G3 EMP installation and connection quick start guide

Eaton ePDU G3 installation and connectivity quick start guide

Service and troubleshooting
EMI319-10 eNMC replacement configuration file

Specifications and datasheets
Eaton Specification Sheet - EMI319-10



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia