

# Product data sheet

Specifications



## 4-Pole Circuit Breaker, 60A, T1 Type for Symmetra PX250/500kW

PD4P60AT1B

### Overview

**Lead time** Usually Ships within 6 Weeks

### Main

**Main Input Voltage** 480 V 3 phase  
400 V 3 phase

**Output connector type** Hard Wire 4-wire (3PH + N) 1

**Provided Equipment** Installation guide

### Physical

**Height** 17.01 in (43.2 cm)

**Width** 22.01 in (55.9 cm)

**Depth** 21.50 in (54.6 cm)

**Product Weight** 4.01 lb(US) (1.82 kg)

**Mounting Location** Front

**Mounting preference** No preference

**Mounting Mode** Not rack-mountable

### Input

**Max line current** 60 A

**Input Frequency** 50 Hz  
60 Hz

### Output

**Maximum Total Current Draw per Phase** 60 A

### Conformance

**Product Certifications** CE  
UL Listed

### Environmental

**Ambient air temperature for operation** 32...104 °F (0...40 °C)

**Relative Humidity** 0...95 %

**Operating altitude** 0...3333 ft

**Ambient Air Temperature for Storage** 5...104 °F (-15...40 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Storage Relative Humidity	0...95 %
---------------------------	----------

---

Storage altitude	0...15000 ft (0.0000000000...4572.0000000000 m)
------------------	---

---

## Ordering and shipping details

---

GTIN	731304277965
------	--------------

---

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	17.01 in (43.2 cm)
------------------	--------------------

---

Package 1 Width	21.50 in (54.6 cm)
-----------------	--------------------

---

Package 1 Length	22.01 in (55.9 cm)
------------------	--------------------

---

Package 1 Weight	6.0 lb(US) (2.7 kg)
------------------	---------------------

---

## Contractual warranty

---

Warranty	1 year repair or replace
----------	--------------------------

---

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No