

# Product data sheet

Specifications



Dry contact, Management Options, Dry Contact I/O Accessory, additional dry contact input and relay outputs

AP9810

Product availability: Stock - Normally stocked in distribution facility

## Overview

Presentation	UPS management accessory that provides two dry contact input and one relay output interface to APC UPS management offers with UIO ports such as the UPS Network Management Card (AP9641, AP9643) or Dry Contact I/O SmartSlot Card (AP9613).
Lead time	Usually in Stock

## Main

Range of Product	Management Options and Cables
Provided Equipment	Cat 5 ethernet cable User Manual
Product or Component Type	Dry contact

## Complementary

Maximum Total Current Draw per Phase	40 mA
Input voltage	24 V
Output voltage	12 V 25 mA DC

## General

Power supply type	Self powered via UPS interface port
-------------------	-------------------------------------

## Physical

Product Weight	0.31 lb(US) (0.14 kg)
Width	10.00 in (25.4 cm)
Height	1.30 in (3.3 cm)
Depth	1.76 in (4.46 cm)
Mounting preference	No preference

## Conformance

Standards	EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-6
-----------	--

## Environmental

Storage Relative Humidity	0...95 %
---------------------------	----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Ambient air temperature for operation	32...104 °F (0...40 °C)
Storage altitude	0...15000 ft (0.0000000000...4572.0000000000 m)
Operating altitude	0...10000 ft 0...50000 ft

## Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304274032
Returnability	No
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.30 in (3.300 cm)
Package 1 Width	10.00 in (25.400 cm)
Package 1 Length	5.00 in (12.700 cm)
Package 1 Weight	4.938 oz (140.000 g)
Unit Type of Package 2	PAM
Number of Units in Package 2	576
Package 2 Height	48.43 in (123.000 cm)
Package 2 Width	47.24 in (120.000 cm)
Package 2 Length	39.37 in (100.000 cm)
Package 2 Weight	178.486 lb(US) (80.960 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **68**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

SCIP Number **1cdb2fed-a06f-4574-913d-8df8e70936b2**

REACH Regulation [REACH Declaration](#)

Halogen content performance **Product contains halogen above thresholds**

### Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **Yes**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**