

Product data sheet

Specifications



Galaxy VL UPS 300 scalable to 500 kW, 400/480V, Start-up 5x8

GVL300K500DS

Overview

Presentation	Highly efficient, modular, high-density 300kW (400/480V) 3-phase UPS that is scalable up to 500kW. It delivers top performance for medium, large, and edge data centers, as well as critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service.
Lead time	Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	380 V 3 phase 400 V 3 phase 415 V 3 phase 440 V 3 phase
Main Output Voltage	380 V 3 phase 400 V 3 phase 415 V 3 phase 440 V 3 phase 480 V 3 phase
Other Output Voltage	400 V 480 V
Kw Rating	300 kW
Rated power in VA	300 kVA
Battery Type	Li-Ion (Lithium Ion) VRLA Ni-Cd (Nickel-Cadmium)
Range of Product	Galaxy VL
Range Compatibility	Galaxy VL

Batteries & Runtime

Efficiency	View Efficiency Graph
End of Discharge Battery Voltage	384 V

General

Number of power module	6
Number of power module free slots	4
Redundant	Yes
Product or Component Type	Uninterruptible power supply (UPS)

Physical

color	White
--------------	-------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	77.6 in (197 cm)
Width	33.5 in (85 cm)
Depth	36.4 in (92.5 cm)
Net Weight	1380.09 lb(US) (626 kg)

Input

Input Frequency	40 - 70 Hz
Maximum Short Circuit Withstand (I _{cw})	65 kA
Input Total Harmonic Distortion	Less than 5% for full load
Load power factor	0.5 leading to 0.5 lagging without derating

Output

Max Configurable Power (Watts)	500 kW
Crest factor	3
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Maximum configurable power in VA	500 kVA

Conformance

Product Certifications	IEC 62040-1-1 UL 1778 5th edition IEC 62040-2 IEC 62040-3 VFI-SS-111 FCC Class A ENERGY STAR V2.0 (USA)
Standards	IEC 60721-4-2 Level 2M2

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...9842.52 ft (0...3000 m)
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)
Storage Relative Humidity	10...80 %
IP degree of protection	IP20

Communications & Management

Control panel	Touch Screen LCD User Interface
---------------	---------------------------------

Ordering and shipping details

GTIN	731304423058
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.4 in (2145 mm)

Package 1 Width	43.3 in (1100 mm)
Package 1 Length	37.4 in (950 mm)
Package 1 Weight	1640.2 lb(US) (744 kg)

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
-----------------	-------------------------------------------------------------------

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)




Transparency RoHS/REACH

Well-being performance

 **Rohs Exemption Information** [Yes](#)

Environmental Certifications

 **Energy Star®** [ENERGY STAR UPS V2.0 \(USA\)](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant with Exemptions](#)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

Image of product / Alternate images

Alternative

