

Product data sheet

Specifications



CDU Flexible Fluid Piping - 300 Feet (91.4 Meters)

ACAC20002

Overview

Lead time Usually Ships within 4 Weeks

General

Provided Equipment	Installation guide
Maximum Recommended Flow Rate	18.5 gal(US)/min (1.2 l/s)
Piping Material	PEX-AL-PEX
Pressure Rating	150 psi (1034.2 kPa)
Fluid connection type	Unterminated
Minimum bending radius	8 in (203.2 mm)
Minimum Fluid Temperature	6 °C (42 °F)
Maximum Fluid Temperature	16 °C (60 °F)
Pressure Drop per foot (0.305m)	0.13 ft of water/ft @ 13.95 gal(US)/min (0.88 l/s)

Physical

Length	300 ft (91.4 m)
Color	White
Depth	42.008 in (106.7 cm)
Height	11.0 in (27.9 cm)
Net Weight	83.18 lb(US) (37.73 kg)
Width	42.008 in (106.7 cm)

Ordering and shipping details

GTIN 731304241621

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.5 in (31.8 cm)
Package 1 Width	45.5 in (115.6 cm)
Package 1 Length	45.5 in (115.6 cm)
Package 1 Weight	87.19 lb(US) (39.55 kg)
Number of Units in Package 3	6

Contractual warranty

Warranty

1 year (parts only)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Not applicable, out of EU RoHS legal scope

Image of product / Alternate images

Alternative

