



GSM4INT 4G Cellular Gateway (AlphaRefuge™ Series)



GSM4INT 4G CELLULAR GATEWAY (ALPHAREFUGE™ SERIES)



ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The 4G Cellular Gateway unit(s) shall be Alpha Communications® **GSM4INT AlphaRefuge™** Series, or approved equal.

The **GSM4INT** shall install in a suitable location and shall be powered by a standard 120vac electrical outlet. When used with the **AlphaRefuge™** Series Area of Refuge system(s) the unit shall provide a 4G Cellular Gateway required.

Contractor shall observe all local and national electrical and building codes.

FEATURES

- GSM Carriers are AT&T or a pre-paid SIM Card
- Requires a "voice" plan (no voicemail)
- End user contracts directly with cellular provider
- Requires 120vac power with battery backup (model# **PWRGSM4**)
- Requires a 2-wire connection from Alpha Communications® phone to device
- Designed for use with the **AlphaRefuge™** 2100 Series Call Boxes / Command Center Base Stations
- No "line check" feature
- Surface Mounted
- Includes Cellular Antenna

SPECIFICATIONS

Dimensions:	5.25"W (134mm) x 1.625"H (42mm) x 7.75"D (197mm) total depth
--------------------	--

Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
 TOLL-FREE: (800) 666-4800 • Web: www.alphacommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2023 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.