

RIB2401D PREPACKAGED RELAY

As one of our most compact Pilot Relay solutions, the **RIB2401D** is suitable for a dynamic assortment of applications. When you install this rugged component into an electrical system, there is no question that it will perform up to expectations. It's durable, easy to install, and capable of adapting to a wide range of physical conditions, including extreme temperatures.

NEMA 1 HOUSING
Promotes safety and durability in multiple environments.

10 AMP DPDT
Offers versatile switching capabilities.

TWO COIL VOLTAGES
Accommodates 24 Vac/dc or 120 Vac.



NEMA 4 HOUSING
RIB2401D-N4



RED HOUSING
RIB2401D-RD



HI/LO VOLTAGE SEPARATION
RIB2401D

Contact Ratings:

- 10 Amp Resistive @ 30 Vdc
- 10 Amp General Use @ 277 Vac
- 1/2 HP @ 120/240 Vac (N/O)
- 1/3 HP @ 120/240 Vac (N/C)
- B300 Pilot Duty
- 120 Vac 30A Make 3A Break (360 VA)
- 240 Vac 15 A Make 1.5A Break (360 VA)
- 208 Vac 17.3A Make 1.73A Break (360 VA)
- 277 Vac 13A Make 1.3A Break (360 VA)
- 24 Vac 30A Make 5A Break (120VA) 5A Max

Coil Current:

- 24 mA @ 18 Vac
- 32 mA @ 24 Vac
- 40 mA @ 30 Vac
- 31 mA @ 120 Vac
- 20 mA @ 20 Vdc
- 24 mA @ 24 Vdc
- 36 mA @ 30 Vdc

Coil Voltage Input:

- 24 Vac/dc ; 120 Vac ; 50-60 Hz
- Drop Out = 3 Vac / 3.8 Vdc
- Pull In = 18 Vac / 20 Vdc

