

# Product data sheet

Specifications

## APC IT Power Distribution Module 3 Pole 5 Wire 30A L21-30 1680cm



PDM3530L2130-1680

### Overview

**Presentation** Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

**Lead time** Usually in Stock

### Main

**Main Input Voltage** 208 V 3 phase

**Main Output Voltage** 120 V

**Provided Equipment** Installation guide

### Physical

**Color** Black

**Height** 5.0000000000 in (12.7 cm)

**Width** 17.5 in (44.5 cm)

**Depth** 16.0 in (40.6 cm)

**Net Weight** 9.46 lb(US) (4.29 kg)

### Input

**Input Frequency** 60 Hz

**Permissible voltage** 200...240 V

**Max line current** 30 A

### Output

**Maximum Total Current Draw per Phase** 30 A

**Number of power socket outlets** 1 NEMA L21-30

### Conformance

**Product Certifications** UL Listed

### Ordering and shipping details

**GTIN** 731304272489

### Packing Units

**Unit Type of Package 1** PCE

<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.0000000000 in (12.7 cm)
<b>Package 1 Width</b>	16.0 in (40.6 cm)
<b>Package 1 Length</b>	17.5 in (44.5 cm)
<b>Package 1 Weight</b>	11.5 lb(US) (5.2 kg)

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Take-back   Transparency

## Resource performance

Take-Back Program Available

---

## Well-being performance

Mercury Free

---

**Reach Regulation**

[REACH Declaration](#)

---

**Eu Rohs Directive**

Under investigation

---

**Environmental Disclosure**

[Product Environmental Profile](#)

---

**Circularity Profile**

[End of Life Information](#)

---