



**Product:** [1476A](#)

Inst, 8 Pr #18+22 Str BC, PVC Ins E1, IS/OS, Blk PVC Jkt, 300V PLTC ITC CMG

[Request Sample](#)

Product Description

UL Instrumentation, 8 Pair 18+22AWG (7x26+7x30) Bare Copper, PVC Insulation E1 Color Code, Individual & Overall Beldfoil® Shield, Black PVC Outer Jacket, PLTC ITC CMG AWM 2464 SUN RES

Technical Specifications

Product Overview

|                        |                                                                                                                                                                                                                                                                                           |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | Industrial Control, Raceways Cable trays and ducts, Digital Control, Instruments (4-20ma, 0-10v, ...),low voltage digital control (24v, ...), encoders, control circuits, distributed control system (DCS),programmable logic controller (PLC), Solenoids, Valves, Actuators, Positioners |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Construction Details

Conductor

| Element      | No. of Elements | Size   | Stranding | Material         |
|--------------|-----------------|--------|-----------|------------------|
| Pair(s)      | 8               | 18 AWG | 7x26      | BC - Bare Copper |
| Comm Wire(s) | 1               | 22 AWG | 7x30      | BC - Bare Copper |

Insulation

| Element      | Material                 | Nom. Thickness     | Color Code                |
|--------------|--------------------------|--------------------|---------------------------|
| Pair(s)      | PVC - Polyvinyl Chloride | 0.017 in (0.43 mm) | Black, White and Numbered |
| Comm Wire(s) | PVC - Polyvinyl Chloride | 0.019 in (0.48 mm) | Orange                    |

Inner Shield

| Element      | Shield Type | Material                | Coverage | Drainwire Type   | Notes     |
|--------------|-------------|-------------------------|----------|------------------|-----------|
| Pair(s)      | Tape        | Bi-Laminate (Alum+Poly) | 100%     | 20 AWG (7x28) TC | each pair |
| Comm Wire(s) | No Shield   |                         |          |                  |           |

Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type   |
|-------------|-------------------------|----------|------------------|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 18 AWG (7x26) TC |

Outer Jacket

| Material                 | Nom. Thickness    | Nom. Diameter      | Ripcord |
|--------------------------|-------------------|--------------------|---------|
| PVC - Polyvinyl Chloride | 0.063 in (1.6 mm) | 0.640 in (16.3 mm) | Yes     |

|                                   |                    |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.640 in (16.3 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

Electricals

| Element      | Nom. Conductor DCR            | Max. Current                  |
|--------------|-------------------------------|-------------------------------|
| Pair(s)      | 5.86 Ohm/1000ft (19.2 Ohm/km) | 2.5 Amps per conductor @ 25°C |
| Comm Wire(s) | 14.7 Ohm/1000ft (48.2 Ohm/km) |                               |

Voltage

| UL Voltage Rating                           |
|---------------------------------------------|
| 300 V (PLTC, CMG, UL AWM 2464), 150 V (ITC) |

Mechanical Characteristics

Temperature

| UL Temperature | Operating       |
|----------------|-----------------|
| 105°C          | -30°C to +105°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 6.4 in (160 mm) | 6.4 in (160 mm)   |

|                    |                  |
|--------------------|------------------|
| Max. Pull Tension: | 501 lbs (227 kg) |
| Bulk Cable Weight: | 236 lbs/1000ft   |

Standards and Compliance

|                                  |                                                                                                                           |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Environmental Suitability:       | Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial                                                              |
| Flammability / Reaction to Fire: | UL1685 (FT4 Loading), FT4, T-29-520, 1202                                                                                 |
| NEC / UL Compliance:             | Article 725, Article 727, Article 800, CMG, ITC, PLTC                                                                     |
| AWM Compliance:                  | AWM 2464                                                                                                                  |
| CEC / C(UL) Compliance:          | CMG                                                                                                                       |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)                                                                                           |

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.582 Revision Date: 01-04-2024 |
|----------------------|--------------------------------------------------|

Part Numbers

Variants

| Item #        | Color       | Putup Type | Length   | UPC          | Footnote |
|---------------|-------------|------------|----------|--------------|----------|
| 1476A 0105000 | Black       | Reel       | 5,000 ft | 612825115434 | C Z      |
| 1476A 0061000 | Blue, Light | Reel       | 1,000 ft | 612825115427 | C        |

© 2024 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.