

# Product data sheet

Specifications



## APC IT Power Distribution Module 2 Pole 3 Wire 30A L2-L3 L6-30 1200CM

PDM2330L6-23-1200

### Overview

**Presentation** Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

**Lead time** Usually Ships within 3 Weeks

### Main

**Main Input Voltage** 208 V

**Main Output Voltage** 208 V

**Provided Equipment** Installation guide

### Physical

**Color** Black

**Height** 5.0000000000 in (12.7 cm)

**Width** 17.5 in (44.4 cm)

**Depth** 16.0 in (40.6 cm)

**Net Weight** 9.46 lb(US) (4.29 kg)

### Input

**Input Frequency** 60 Hz

**Max line current** 30 A

### Output

**Maximum Total Current Draw per Phase** 30 A

**Number of power socket outlets** 1 NEMA L6-30R

### Conformance

**Product Certifications** UL Listed

### Environmental

**Ambient Air Temperature for Operation** 32...86 °F (0...30 °C)

**Relative Humidity** 0...95 %

**Operating altitude** 0...10000 ft

**Ambient Air Temperature for Storage** 5...104 °F (-15...40 °C)

---

<b>Storage Relative Humidity</b>	0...95 %
----------------------------------	----------

---

<b>Storage altitude</b>	0...15000 ft (0.0000000000...4572.0000000000 m)
-------------------------	---

---

## Ordering and shipping details

---

<b>GTIN</b>	731304286059
-------------	--------------

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	5.0000000000 in (12.7 cm)
-------------------------	---------------------------

---

<b>Package 1 Width</b>	16.0 in (40.6 cm)
------------------------	-------------------

---

<b>Package 1 Length</b>	17.5 in (44.4 cm)
-------------------------	-------------------

---

<b>Package 1 Weight</b>	11.5 lb(US) (5.2 kg)
-------------------------	----------------------

## Contractual warranty

---

<b>Warranty</b>	1 year repair or replace
-----------------	--------------------------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)




Take-back Transparency RoHS/REACH

## Resource performance


 Take-Back Program Available

---

## Well-being performance

 Mercury Free

---

 RoHS Exemption Information [Yes](#)

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive Compliant with Exemptions

---

Environmental Disclosure [Product Environmental Profile](#)

---

Circularity Profile [End of Life Information](#)

---

Image of product / Alternate images

Alternative

---

