**inSIGHT™ Data Com Rack Power Distribution Unit**

## Basic Power Distribution

## Complete line of single and three phase PDUs

HUBBELL

### Features

- Locking standard cords to prevent inadvertent disconnection
- High reliability with robotically soldered connections
- Available in Black, Blue, Red, and White



### Ordering Information

| Type | Nominal | Catalog Number | UPC |
|---|---|---|---|
| Basic always on powering | 208V Three Phase | **PV72BD30FD-10BL** | 662620365541 |

### Listings

UL 2416
EIA 310-E Universal Mounting Pattern
UL 60950-1

### Specifications

| | |
|---|---|
| Input Current (A) | 30 Amp |
| Input Power Cord | L15-30P Plug |
| Receptacle group | 36 C13 & 6 C19 Receptacle |
| PDU Size | 72" vertical mount |
| Regulatory Approval | TUV Certified to UL / CSA 609050-1 |
| Operating Environment | 0 to 60 |
| Storage Environment | -25 to 65 |
| PDU Dimension (inches) | 72 length X 2.2 width X 4.8 depth |

### Performance

**Low profile**

2.18" X 2". Improves airflow

**Receptacle Locking**

Prevents inadvertent disconnections. Secured with standard cords

### Online Resources

eCatalog