

# Product data sheet

Specifications



## Rack PDU, Basic, 1U, 20A, 120V, (10)5-20; L5-20P

AP9564

**Product availability: Stock - Normally stocked in distribution facility**

### Overview

**Lead time** Usually in Stock

### Main

<b>Color</b>	Black
<b>Product or Component Type</b>	PDU
<b>PDU Type</b>	Basic
<b>Cord length</b>	12 ft (3.7 m)
<b>Number of cables</b>	1
<b>Provided Equipment</b>	Installation guide Rack Mounting brackets

### Complementary

<b>Input Voltage</b>	100 V 120 V
<b>Height</b>	1.73 in (4.4 cm)
<b>Width</b>	17.60 in (44.7 cm)
<b>Output Voltage</b>	120 V
<b>Depth</b>	2.24 in (5.7 cm)
<b>Product Weight</b>	5.5 lb(US) (2.5 kg)
<b>Mounting Location</b>	Front Rear
<b>Mounting preference</b>	No preference
<b>Input Plug Type</b>	NEMA L5-20P
<b>Mounting Mode</b>	Rack-mounted
<b>Rack units</b>	1U
<b>Mounting position</b>	Horizontal
<b>Line Rated Current</b>	16 A
<b>Input current limits</b>	20 A
<b>Load Capacity</b>	1920 VA
<b>Input Frequency</b>	50/60 Hz
<b>Outlet type and quantity</b>	10 NEMA 5-20R

### Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Product Certifications</b>	cUL Listed UL Listed
<b>Ambient air temperature for operation</b>	23...113 °F (-5...45 °C)
<b>Relative Humidity</b>	0...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13...149 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	0...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>Category</b>	11309-APC RESALE PRODUCTS
<b>Discount Schedule</b>	APC1
<b>GTIN</b>	731304203872
<b>Returnability</b>	No
<b>Country of origin</b>	IN

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	2.76 in (7 cm)
<b>Package 1 Width</b>	9.02 in (22.9 cm)
<b>Package 1 Length</b>	18.27 in (46.4 cm)
<b>Package 1 Weight</b>	8.02 lb(US) (3.64 kg)

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 64

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

### Energy efficiency

Optimized Energy Efficiency Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

Image of product / Alternate images

Alternative

---

