Product data sheet

Specifications



Symmetra PX 250/500kW UL Battery Breaker Enclosure for Third Party Batteries

SYBBE-UL

Overview

Lead time	Usually Ships within 6 Weeks

Main

Battery Type	External battery system
Provided Equipment	User Manual

Physical

Color	Black
Height	78.4 in (199.1 cm)
Width	23.6 in (60 cm)
Depth	42.1 in (107 cm)
Net Weight	720.9 lb(US) (327 kg)

Conformance

Product Certifications	UL Listed

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Operating altitude	0...3333 ft
Relative Humidity	0…95 %
Ambient Air Temperature for Storage	5…104 °F (-15…40 °C)
Storage altitude	0…15000 ft (0.0000000000…4572.0000000000 m)
Storage Relative Humidity	0…95 %

Ordering and shipping details

GTIN	731304338161

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.06 in (213.5 cm)
Package 1 Width	47.6 in (121 cm)
Package 1 Length	29.5 in (75 cm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	804.7 lb(US) (365 kg)

Contractual warranty

Warranty	1 year repair or replace

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Learn more about Green Premium >




Energy Efficient Take-back

Resource performance

- Energy Efficient Product
- Take-Back Program Available

Well-being performance

- Mercury Free
- Rohs Exemption Information — Yes

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)

Image of product / Alternate images

Alternative



