Product data sheet

Specifications



APC IT Power Distribution Module 3 Pole 5 Wire 30A L21-30 680cm

PDM3530L2130-680

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phase
Main Output Voltage	120 V
Provided Equipment	Installation guide

Physical

Color	Black
Height	5.0000000000 in (12.7 cm)
Width	17.5 in (44.5 cm)
Depth	16.0 in (40.6 cm)
Net Weight	11.42 lb(US) (5.18 kg)

Input

Input Frequency	60 Hz
Permissible voltage	200…240 V
Max line current	30 A

Output

Maximum Total Current Draw per Phase	30 A
Number of power socket outlets	1 NEMA L21-30

Conformance

Product Certifications	UL Listed

Ordering and shipping details

GTIN	731304272458

Packing Units

Unit Type of Package 1	PCE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	5.0000000000 in (12.7 cm)
Package 1 Width	16.0 in (40.6 cm)
Package 1 Length	17.5 in (44.5 cm)
Package 1 Weight	12.63 lb(US) (5.73 kg)

Contractual warranty

Warranty	1 year repair or replace

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Learn more about Green Premium >




Take-back Transparency

Resource performance

Take-Back Program Available

Well-being performance

Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information