Product data sheet

Specifications



Power Cord Kit (6 EA), Locking, C19 TO C20, 1.2M (4FT), Red

AP8714SX340

Overview

Lead time	Usually in Stock

Main

Product or Component Type	Power cord
Input Connection Type	IEC 60320 C20
Cable length	4 ft (1.2 m)
Number of cables	6

Physical

Color	Red
Height	11.81 in (30 cm)
Width	2.76 in (7 cm)
Depth	2.76 in (7 cm)
Product Weight	3.62 lb(US) (1.64 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Maximum Total Current Draw per Phase	16 A
Number of power socket outlets	1 IEC 60320 C19
Cord Length	4 ft (1.2 m)

Conformance

Product Certifications	CCC CSA PSE UL Listed VDE

Environmental

Ambient air temperature for operation	32…167 °F (0…75 °C)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative Humidity	20…80 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13…167 °F (-25…75 °C)
Storage Relative Humidity	20…80 %
Storage altitude	0…50000 ft (0.0000000000…15240.0000000000 m)

Ordering and shipping details

GTIN	731304329428
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.81 in (30 cm)
Package 1 Width	2.76 in (7 cm)
Package 1 Length	2.76 in (7 cm)
Package 1 Weight	3.62 lb(US) (1.64 kg)

Contractual warranty

Warranty	2 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency	Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	Yes

Image of product / Alternate images

Alternative

