

Product data sheet

Specifications



Rack PDU, Basic, Zero U, 10A, 230V, (15)C13



AP9568

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Basic

Cord length 6.5 ft (2.0 m)

Number of cables 1

Provided Equipment Installation guide
Rack Mounting brackets
Toolless Mounting Kit

Complementary

Input Voltage 120 V
200 V
208 V
230 V
240 V

Height 24.02 in (61 cm)

Width 1.73 in (4.4 cm)

Output Voltage 208 V
230 V

Depth 1.73 in (4.4 cm)

Product Weight 4.4 lb(US) (2 kg)

Mounting Location Side

Mounting preference No preference

Input Plug Type IEC 60320 C14

Mounting Mode Rack-mounted

Rack units 0U

Mounting position Vertical

Acceptable Input Voltage 100...240 V

Input current limits 10 A

Load Capacity 2300 VA

Input Frequency 50/60 Hz

Outlet type and quantity 15 IEC 60320 C13

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product Certifications	cUL Listed CE GOST Queensland Australia UL Listed VDE
Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304207054
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.51 in (64.8 cm)
Package 1 Width	7.01 in (17.8 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	6.005 lb(US) (2.724 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 51

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

Halogen content performance Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

