# Isobar 2-Outlet Surge Protector, Direct Plug-In, 1410 Joules, Diagnostic LEDs, Metal Housing

MODEL NUMBER: **ISOBLOK2-0**












Premium protection for A/V home theater components and computer peripherals against dangerous power surges, spikes and line noise. Recommended for home theaters and home offices.

## Highlights

- 2 NEMA 5-15R surge-protected outlets
- 1410-joule surge protection rating
- Durable metal housing mounts out of sight behind furniture
- LEDs indicate power, protection and line fault status
- Plugs directly into outlet with no power cord

## Package Includes

- ISOBLOK2-0 Isobar 2-Outlet Surge Protector, Metal Housing
- Mounting hardware
- Owner's manual

## Description

Premium protection for your expensive computer and audio/visual equipment, the ISOBLOK2-0 Isobar® 2-Outlet Surge Protector features a surge protection rating of 1410 joules to defend your sensitive electronics against even the strongest surges and spikes.

The ISOBLOK2-0 features two NEMA 5-15R outlets, perfect for your flat-panel HDTV and Blu-ray™ player or a pair of computer peripherals, such as a printer and a router. This unit's unique protection system prevents disruptive line noise from causing A/V distortion, computer lock-ups, data errors and similar problems. Large toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors remove EMI/RFI interference and prevent system crashes, reboots and performance problems.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the ISOBLOK2-0 protects all three, covering two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

Diagnostic LEDs show power, protection and line fault status at a glance. The ISOBLOK2-0 plugs directly into any standard NEMA 5-15R outlet. Optional mounting hardware is included for permanent attachment to the outlet cover, which will prevent the ISOBLOK2-0 from coming loose accidentally.

## Features

**1410-Joule Surge Protection for Your Home Theater Electronics and Computer Peripherals**

- Protects your components against surges and spikes
- Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- 2 NEMA 5-15R surge-protected outlets

**Premium Safety Features**

- Diagnostic LEDs confirm power, protection and ground status at a glance
- Conforms to current UL 1449 3rd Edition safety standards
- Auto shutoff cuts power to outlets when the protection circuit is compromised

**Fits Effortlessly Into Your Setup**

- Plugs directly into standard NEMA 5-15R outlet with no power cord
- Optional hardware included for permanent mounting to outlet cover
- Metal housing designed for long life

**Backed by Ultimate Lifetime Insurance**

- $10,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

# Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332010155 |
| **INPUT** | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input Cord Length Details | Direct Plug-In |
| Voltage Compatibility (VAC) | 120 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Length (ft.) | 0 |
| Right-Angle Plug | No |
| Input Cord Length (m) | 0.00 |
| Integrated Cord Clip | No |
| **OUTPUT** | |
| Frequency Compatibility | 50 / 60 Hz |
| Output (Watts) | 1800 |
| Output Receptacles | (2) 5-15R |
| Circuit Breaker (amps) | 15 |
| Right-Angle Outlets | No |
| **USER INTERFACE, ALERTS & CONTROLS** | |
| Diagnostic LED(s) | Yes |
| Diagnostic LED Details | PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green) |
| **SURGE / NOISE SUPPRESSION** | |
| AC Suppression Joule Rating | 1410 |
| AC Suppression Response Time | NM = 0 ns. CM = <1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| AC Suppression Surge Current Rating | 48,000 amps |
| AC Suppression Components Used | Metal oxide varistors, toroidal balanced chokes and VHF capacitors |

| | |
|---|---|
| Safe Thermal Fusing | Prevents unsafe conditions during extreme extended overvoltages and catastrophic occurences |
| UL1449 Let Through Rating | 330V |
| EMI / RFI Filtering | 40-80 dB |
| Isolated Filter Banks | y |
| Immunity | Conforms to IEE 587 / ANSI C62.41 |
| Automatic Shut-Off | No |
| **DATALINE SURGE SUPPRESSION** | |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| Telephone/DSL Protection | No |
| **PHYSICAL** | |
| Material of Construction | Metal |
| Form Factors Supported | Direct plug-in format with retaining bracket supports wall mounting directly to a standard AC wall socket |
| Housing Color | Gray |
| Mounting Holes or Slots | No |
| Receptacle Color | Black |
| Shipping Dimensions (hwd / in.) | 2.50 x 6.00 x 3.90 |
| Shipping Dimensions (hwd / cm) | 6.35 x 15.24 x 9.91 |
| Shipping Weight (lbs.) | 0.80 |
| Shipping Weight (kg) | 0.36 |
| Unit Dimensions (hwd / in.) | 4.000 x 2.500 x 2.500 |
| Unit Dimensions (hwd / cm) | 10.2 x 6.4 x 6.4 |
| Unit Weight (lbs.) | 0.8 |
| Unit Weight (kg) | 0.36 |
| **FEATURES & SPECIFICATIONS** | |
| Rotatable Outlets | No |
| Antimicrobial | No |
| **STANDARDS & COMPLIANCE** | |
| Product Certifications | NOM (Mexico); UL 1449; UL 1363 |
| Product Compliance | RoHS |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

| | |
|---|---|
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | $10,000 <a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>  |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.