

# Product data sheet

Specifications



## APC Back-UPS 600VA, 120V, 1 USB charging port, 7 NEMA outlets (2 surge)

BE600M1

Product availability: Stock - Normally stocked in distribution facility

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	330 W
Rated power in VA	600 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	5 NEMA 5-15R 2 NEMA 5-15R surge
Cable length	5 ft (1.5 m)
Battery Type	Lead-Acid battery
Provided equipment	User Manual
Range of Product	Back-UPS

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	10 h
RBC Quantity	1
Battery Voltage	12 V
Battery Charge Power (Watts)	7 W rated
Battery power in VAh	66 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC154</a>
Extendable Run Time	0

### General

Number of power module free slots 0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of power module filled slots	0
Redundant	No

## Physical

color	Black
Height	5.47 in (13.9 cm)
Width	10.79 in (27.4 cm)
Depth	4.13 in (10.5 cm)
Product Weight	7.69 lb(US) (3.49 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	92...139 V

## Output

Max Configurable Power (Watts)	330 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	600 VA
Transfer Time	6ms typical : 10ms maximum

## Conformance

Product Certifications	California (CEC) Battery Charger cTUVus NOM
------------------------	---

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...90 %
Operating altitude	0...3000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...5000 ft (0.0000000000...1524.0000000000 m)
Acoustic level	35 dBA
Online Thermal Dissipation	16 Btu/h

## Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

---

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
--------------	--

## Surge Protection and Filtering

---

<b>Surge energy rating</b>	490 J
<b>Filtering</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
<b>Let Through Voltage Rating</b>	5 V

---

## Ordering and shipping details

---

<b>Category</b>	11309-APC RESALE PRODUCTS
<b>Discount Schedule</b>	APC1
<b>GTIN</b>	731304325116
<b>Returnability</b>	No

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7.72 in (19.6 cm)
<b>Package 1 Width</b>	6.61 in (16.8 cm)
<b>Package 1 Length</b>	14.29 in (36.3 cm)
<b>Package 1 Weight</b>	8.40 lb(US) (3.81 kg)
<b>SCC14</b>	10731304325113

---

## Contractual warranty

---

<b>Warranty</b>	3 years repair or replace
-----------------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

California proposition 65

**WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Energy efficiency

Optimized Energy Efficiency

Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

Take-back

Yes

Technical Illustration

Dimensions

---



Offer Marketing Illustration

Product benefits / Features

---



Image of product / Alternate images

Alternative

---



