

# SELF-AMPLIFIED SURFACE MOUNTED SPEAKER COMBOS

**AMP6022**

(1) EACH SELF-AMPLIFIED SPEAKER WITH A 115 VOLT POWER SUPPLY AND (1) EACH NON-AMPLIFIED SPEAKER P602

**AMPLV6022**

(1) EACH SELF-AMPLIFIED, LOW VOLTAGE SPEAKER WITH A UL LISTED, 15 VDC, LEVEL **V** POWER SUPPLY AND (1) EACH NON-AMPLIFIED SPEAKER P602



**PERFECT FOR SCHOOLS, HOTELS, CONFERENCE ROOMS AND TRAINING ROOMS.**

**AMP6022 (High Voltage Combo)**  
Self-Amplified Speaker with a  
115 Volt Power Supply and  
a Non-Amplified Speaker P602

**AMPLV6022 (Low Voltage Combo)**  
Self-Amplified Speaker with a  
Low Voltage 15 VDC, Level **V** Power  
Supply and a Non-Amplified Speaker P602



AMP602W CE P602W



AMPLV602B CE P602B

## FEATURES:

- Two Speakers – 6.5" Woofer Active (Self-Amplified) and Passive
- 15 Watts x 2 = 30 Watts Power
- 0.79" (20mm) Tweeter
- Impedance: 4 Ω
- Dispersion: 92°
- "U" Mounting Bracket Included
- CE Approved
- Weight: 12 Lbs. (Amplified)  
10 Lbs. (Non-Amplified)
- Dimensions: 9.5"H x 8.46"W x 11.3"D  
(242 x 215 x 288 mm)
- White or Black (Paintable)
- Sold as "Each" or in Combo
- 1 Year Warranty

**OWI**<sup>®</sup>  
OWI Incorporated  
Established 1978

# SELF-AMPLIFIED SURFACE MOUNTED SPEAKER COMBOS

**AMP6022**

(1) EACH SELF-AMPLIFIED SPEAKER WITH A 115 VOLT POWER SUPPLY AND (1) EACH NON-AMPLIFIED SPEAKER P602

**AMPLV6022**

(1) EACH SELF-AMPLIFIED, LOW VOLTAGE SPEAKER WITH A UL LISTED, 15 VDC, LEVEL **V** POWER SUPPLY AND (1) EACH NON-AMPLIFIED SPEAKER P602

**PASSIVE SPEAKER MODEL: P602**

Description: ..... 6.5" Passive Cabinet Speaker  
 Outdoor: ..... No  
 Impedance: ..... 4 Ω  
 Dispersion: ..... 92°  
 Sensitivity (1W / 1M): ..... 86 dB  
 Maximum Power: ..... 30 W  
 Nominal Power: ..... 15 W  
 Frequency Response: ..... 80 Hz - 20 kHz  
 Crossover: ..... 3.5 kHz  
 High Frequency Driver: ..... 1.5 kHz - 6 kHz  
 Low Frequency Driver: ..... 80 Hz - 6 kHz  
 Woofer Size: ..... 6.5"  
 Woofer Material: ..... Mica / Foam Surround  
 Tweeter Size: ..... .79" (20 mm)  
 Tweeter Material: ..... PEI  
 Enclosure: ..... Plastic Enclosure  
 Dimensions (LxWxH): ..... 9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)  
 CE Approved: ..... Yes  
 Weight (Pounds/Kgs): ..... 10 lbs. (4.5 Kgs)  
 Colors: ..... White or Black  
 Paintable: ..... Yes  
 Warranty: ..... 1 Year



AMP602W **CE** Backside

P602W



AMPLV602B **CE** Backside

P602B

## AMP6022 (High Voltage Combo)

Self-Amplified Speaker with a 115 Volt Power Supply and a Non-Amplified Speaker P602

## AMPLV6022 (Low Voltage Combo)

Self-Amplified Speaker with a Low Voltage 15 VDC, Level **V** Power Supply and a Non-Amplified Speaker P602

**AMPLIFIED SPEAKER MODEL: AMP602**

Description: ..... 6.5" Active  
 Outdoor: ..... No  
 Impedance: ..... 4 Ω  
 Dispersion: ..... 92°  
 Sensitivity (1W / 1M): ..... 83 dB (VR at Max.)  
 Power: ..... 15 W x 2  
 Frequency Response: ..... 80 Hz - 20 kHz  
 Crossover: ..... 3.5 kHz  
 S / N: ..... >80 dB  
 Input Configuration: ..... RCA L / R  
 Input Load Impedance: ..... 20 K Ω  
 Maximum Current Protected: ..... Yes  
 One Wire To Ground Protected: ..... Yes  
 Short Circuit Protected: ..... Yes  
 THD: ..... <0.2%  
 Power Supply: ..... 115 V  
 High Frequency Driver: ..... 1.5 kHz - 20 kHz  
 Low Frequency Driver: ..... 80 Hz - 6 kHz  
 Woofer Size: ..... 6.5"  
 Woofer Material: ..... Mica  
 Tweeter Size: ..... .79" (20 mm)  
 Tweeter Material: ..... PEI  
 Enclosure: ..... High Impact Polystyrene (HIPS)  
 Dimensions (LxWxH): ..... 9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)  
 Weight (Pounds/Kgs): ..... 12 lbs. (5.5 Kgs)  
 CE Approved: ..... Yes  
 Colors: ..... White or Black  
 Paintable: ..... Yes  
 CE Approved: ..... Yes  
 Warranty: ..... 1 Year

**AMPLIFIED SPEAKER MODEL: AMPLV602**

Description: ..... 6.5", 2-Way, Active, Full Range  
 Outdoor: ..... No  
 Impedance: ..... 4 Ω  
 Dispersion: ..... 92°  
 Sensitivity (1W / 1M): ..... 83 dB (VR at Max.)  
 Power: ..... 15 W x 2  
 Maximum Power: ..... 30 W  
 Nominal Power: ..... 15 W  
 Frequency Response: ..... 80 Hz - 20 kHz  
 S/N: ..... >80 dB  
 Input Configuration: ..... RCA L/R  
 Input Load Impedance: ..... 20 K Ω  
 Maximum Current Protected: ..... Yes  
 One Wire to Ground Protected: ..... Yes  
 Short Circuit Protected: ..... Yes  
 THD: ..... <0.2%  
 High Frequency Driver: ..... 1.5 kHz - 20 kHz  
 Low Frequency Driver: ..... 80 Hz - 6 kHz  
 Woofer Size: ..... 6.5"  
 Woofer Material: ..... Mica  
 Tweeter Size: ..... .79" (20 mm)  
 Tweeter Material: ..... PEI  
 Enclosure: ..... High Impact Polystyrene (HIPS)  
 Grill Material: ..... FE  
 Dimensions (LxWxH): ..... 9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)  
 Weight (Pounds/Kgs): ..... 12 lbs. (5.5 Kgs)  
 Colors: ..... White or Black  
 Paintable: ..... Yes  
 Power Supply: ..... 15 VDC, UL Listed, Efficiency Level **V** (Energy Star)  
 (Dimensions: 4.7"H x 2.0"W x 1.2"D)  
 CE Approved: ..... Yes  
 Warranty: ..... 1 Year



AMP6022 (High Voltage Combo)



AMPLV6022 (Low Voltage Combo)