Product datasheet

Specifications



APC Modular IT Power Distribution Cable Extender 3 Wire 16A IEC309 720cm

PDX316IEC-720

Overview

Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60309 16 A 2P + E
Provided equipment	Installation guide

Physical

Height	15.2 cm
Width	43.2 cm
Depth	40.6 cm
Net weight	1.79 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable

Input

Max line current	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60309 16 A 2P + E

Conformance

product certifications	CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.2 cm
Package 1 Width	40.6 cm
Package 1 Length	43.2 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	2.7 kg

Contractual warranty

Warranty	1 year repair or replace

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Eu Rohs Directive	Under investigation