

# Product data sheet

Specifications



APC Back-UPS 1350, Compact Tower, 1350VA, 120V, AVR, LCD, 10 NEMA outlets (5 surge)

BX1350M

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	810 W
Rated power in VA	1350 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	5 NEMA 5-15R 5 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Number of cables	1
Battery Type	Lead-Acid battery
Range of Product	Back-UPS Pro

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	1
Battery Charge Power (Watts)	9 W rated
Extendable Run Time	0
Replacement battery	<a href="#">APCRBC123</a>

## General

Provided equipment	User Manual USB cable
Number of power module free slots	0
Number of power module filled slots	0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Redundant	No
-----------	----

## Physical

Height	9.84 in (25 cm)
Width	3.94 in (10 cm)
Depth	15.04 in (38.2 cm)
Product Weight	22.5 lb(US) (10.2 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Input Frequency	60 Hz +/- 3 Hz
Plug standard	NEMA 5-15P
Efficiency at full load	88...139 V
Maximum Input Current per Phase	12 A
Switching current capacity	15 A

## Output

Max Configurable Power (Watts)	810 W
Output frequency	60 Hz sync to mains
Topology	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	1350 VA
Transfer Time	8ms typical : 10 ms maximum

## Conformance

Product Certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) TUV C-US certified
Equipment protection policy	Lifetime : \$250000

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Acoustic level	45 dBA
Online Thermal Dissipation	67.6 Btu/h

## Communications & Management

---

control panel	Multi-function LCD status and control console
---------------	---

---

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

## Surge Protection and Filtering

---

Surge energy rating	789 J
---------------------	-------

---

Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee
-----------	--

---

Data line protection	Coaxial cable for CATV/SATV/modem/audio-video
----------------------	---

## Ordering and shipping details

---

GTIN	731304331773
------	--------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	13.70 in (34.8 cm)
------------------	--------------------

---

Package 1 Width	19.33 in (49.1 cm)
-----------------	--------------------

---

Package 1 Length	8.94 in (22.7 cm)
------------------	-------------------

---

Package 1 Weight	26.2 lb(US) (11.9 kg)
------------------	-----------------------

---

SCC14	10731304331770
-------	----------------

## Contractual warranty

---

Warranty	3 years repair or replace
----------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

50414655-abe7-48e2-9b8c-578e40cce4a8

REACH Regulation

[REACH Declaration](#)

California proposition 65

**WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Energy efficiency

Optimized Energy Efficiency

Energy efficient product

 [ENERGY STAR®](#)

ENERGY STAR UPS V2.0 (USA)

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

Take-back

Yes

Image of product / Alternate images

Alternative

---



