

Product data sheet

Specifications



APC IT Power Distribution Module 3x1 Pole 3 Wire 32A 3xIEC309 300cm, 360cm, 420cm



PDM1332IEC-3P

Overview

Presentation Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

Lead time Usually Ships within 3 Weeks

Main

Main Input Voltage 400 V 3 phase

Main Output Voltage 230 V

Provided Equipment Installation guide

Physical

Color Gray

Height 6.0 in (15.2 cm)

Width 17.008 in (43.2 cm)

Depth 6.0 in (15.2 cm)

Net Weight 14.09 lb(US) (6.39 kg)

Input

Input Frequency 50 Hz

Max line current 32 A

Output

Maximum Total Current Draw per Phase 32 A

Number of power socket outlets 3 IEC 309 32 A 2P+E

Conformance

Product Certifications CE
VDE

Ordering and shipping details

GTIN 731304257622

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height	6.0 in (15.2 cm)
Package 1 Width	6.0 in (15.2 cm)
Package 1 Length	17.008 in (43.2 cm)
Package 1 Weight	16.09 lb(US) (7.3 kg)

Contractual warranty

Warranty	1 year repair or replace
-----------------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)





Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Mercury Free

 RoHS Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
