



PERISCAPE 4 PRODUCT SPECIFICATIONS

System Type	4.5" 2-way Outdoor Landscape Speaker
Impedance (Nominal) ¹	8 ohm
Sensitivity dB @ 2.83 V / 1 M	83 dB
Sensitivity dB @ 1 W / 1 M ²	83 dB
Frequency Response (±3 dB) ³	85 Hz - 22 kHz
Frequency Response (±10 dB) ³	50 Hz - 22 kHz
Max. Program Power ⁴	100 W
Max. Continuous Power RMS ⁵	50 W
Max. SPL dB @ 1 M ⁶	100dB
Tap Selector	Rotary Switch
Transducer: Low-Frequency Driver	4" Polypropylene Cone with Butyl Rubber Surround
Transducer: High-Frequency Driver	.75" Titanium Dome
Enclosure Material	Injection molded ABS, glass fiber reinforced
Grille	Aluminum, Powder-Coated, Weatherproof
Inputs	Wire leads
Colors	Brown
Length	6.9 in / 175.3 mm
Width	5.5 in / 139.7 mm
Height	18.125 in / 460.4 mm
Weight	4.5 lbs / 2.04 kg
Shipping Weight	5.95 lbs / 2.7 kg
Packaging	One per box
Included Accessories	Mounting Hardware, Wire Nuts
Optional Accessories	Surface Mount Bracket (AC-RPSMB) Pole Mount Extension (AC-RPEXT)
IP Rating	IPX5
Certifications	CE, RoHS, IPX5
TAA Compliant (Trade America)	No
BAA Compliant (Made in USA)	No

Description

With 50 watts (RMS) of power, the Rockustics Periscope 4 from SoundTube gives you an attractive, discreet way to distribute audio throughout an outdoor setting. This 4.5", 2-way speaker is fully weatherproof and is easily installed via a spike mount. Applications include outdoor living spaces, hotel pool areas, courtyards, outdoor malls, or outdoor seating areas for restaurants or cafes. Systems may be configured with any number of Periscope speakers, with a minimum suggested complement of four Periscope units and one Subscape subwoofer; additional subwoofers are recommended for installations using more than eight Periscope speakers. All models have transformers with tap settings for 70.7 or 100 V operation; a transformer bypass setting allows operation in 8 ohm direct mode.

Features

- 4.5", 2-way speaker assembly with 0.75" titanium dome tweeter
- System provides exceptional audio everywhere in the listening environment
- Spike mount allows for easy installation into flowerbeds and other landscaping
- Speaker assembly can be tilted up or down with incrementally-locking elbow joint
- Fully weatherproof speaker system
- 5-position tap switch for easy switching between 70.7V transformer taps and 8-ohm bypass position
- Mid-tweeter assembly can be pivoted up and down.
- Optional Pole Mount Extension (AC-RPEXT) and Surface Mount Bracket (AC-RPSMB)

¹ Impedance listed per IEC 60268-5 with a minimum less than 80% the nominal impedance

² 1 W/1 M sensitivity determined using nominal impedance

³ Frequency response measured in half or full space as dictated by speaker mounting configuration

⁴ Max program power is 3 dB above max continuous power

⁵ Continuous power rating, EIA-426-B test

⁶ Max output based on max continuous power

SoundTube®

13720 W. 109th St.
Lenexa, KS 66215
Phone: 913.663.5600
Fax: 913.663.3200
Toll Free: 855.663.5600
www.soundtube.com

Rockustics Periscope 4

4.5" 2-Way Outdoor Landscape Speaker

