

Product data sheet

Specifications



APC Smart-UPS SRT Tower Isolation/Step-Down Transformer, 5kVA, 8x 5-20R & 2x L6-20R & 1x L6-30R & 1x L14-30R NEMA outlets

SRT5KTf

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Main Input Voltage 208 V
240 V

Product or Component Type Transformer

Main Output Voltage 120 V
208 V

Other Output Voltage 240 V

Input Connection Type NEMA L6-30P

Cable length 3 ft (0.9 m)

Number of cables 1

Provided Equipment User Manual

Range of Product Smart-UPS Accessories

Physical

Color Black

Height 17.01 in (43.2 cm)

Width 5.12 in (13 cm)

Depth 25.98 in (66 cm)

Product Weight 125.002 lb(US) (56.7 kg)

Mounting preference No preference

Mounting Mode Rack-mounted with kit

Input

Input Frequency 50/60 Hz

Output

Maximum Total Current Draw per Phase 5000 A

Number of power socket outlets 12

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of power socket outlets	8 NEMA 5-20R 2 NEMA L6-20R 1 NEMA L6-30R 1 NEMA L14-30R
---------------------------------------	--

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304318873
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.66 in (34.7 cm)
Package 1 Width	38.58 in (98 cm)
Package 1 Length	23.74 in (60.3 cm)
Package 1 Weight	140.0 lb(US) (63.5 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Take-back

Yes

WEEE


 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

