Product data sheet

Specifications



APC Smart-UPS Modular Ultra 15kW Frame, N+1 Redundant, Rackmount, 208/120V

SRYLF15KRMT

Overview

Lead time	Usually in Stock

Main

Main Input Voltage	208 V AC
Product or Component Type	Frame
Main Output Voltage	120 V AC
Rated power in VA	15000 VA
Battery Type	Li-Ion (Lithium Ion)
Range of Product	Smart-UPS Modular Ultra Accessories

General

product web sub-family	Network management card

Physical

color	Silver
Height	15.4 in (390 mm)
Width	17.3 in (440 mm)
Depth	27.6 in (700 mm)
Product Weight	130.3 lb(US) (59.1 kg)

Ordering and shipping details

GTIN	731304420149

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.83 in (58 cm)
Package 1 Width	23.62 in (60 cm)
Package 1 Length	38.66 in (98.2 cm)
Package 1 Weight	154.3 lb(US) (70 kg)

Contractual warranty

Warranty	5 Years

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant with Exemptions**
SCIP Number	**5ee38369-4dfb-4636-ab65-b08aa3242891**
REACh Regulation	**REACh Declaration**

Use Again

Repack and remanufacture

Take-back	**No**