



MXAV333 QwikBUS™ Intelligent Audio/Video Mixer



ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The intelligent audio/video mixer(s) shall be Alpha Communications® / S.T.R.™ QwikBUS™ model **MXAV333**, or approved equal. The **MXAV333** shall be built into a rugged high impact ABS plastic case, and shall be used with the associated **SP333** intelligent controller (and associated **SNT333S** power supply and **C333-2** connecting cable) for up to 100 QwikBUS™ audio stations (25 per line maximum), or up to 40 QwikBUS™ video stations (8-10 per line maximum). Contractor shall furnish the proper number of **MXAV333** and **SP333** units (and related components), depending upon system capacity.

Low voltage wiring shall be used and positive screw terminal and plug-in connectors shall be provided for installation wiring. The **MXAV333** shall be mountable right to the surface of the wall or in a customer supplied junction box cabinet.

Contractor shall observe all local and national electrical and building codes.

MXAV333 QWIKBUS™ INTELLIGENT AUDIO/VIDEO MIXER



The Alpha Communications® / S.T.R.™

MXAV333 intelligent mixer is used primarily with the QwikBUS™ series intercom or video-intercom systems for systems. The **MXAV333** provides the intelligent circuitry needed to install multiples of 100 audio QwikBUS™ stations, or multiples of up to 40 video QwikBUS™ stations, allowing systems with very large system capacities.

Each **MXAV333** gets its power from its associated **SP333** intelligent controller and corresponding **SNT333S** power supply. All **MXAV333** field connections are positive screw terminal type, or plugin type. Each **MXAV333** requires the **SP333** and **SNT333S**, and **C333-2** connecting cable assembly.

The **MXAV333** can also directly replace the older model **MXA333** and/or **MXV333** mixers.

FEATURES

- Easily Installs Right on Finished Wall Surface or in Optional Junction Box
- Operates on Safe Low-Voltage Class II Wiring
- Positive Screw Terminal Connectors

SPECIFICATIONS

Dimensions:	Height: 3.75" (96mm) Width: 4.25" (108mm) Depth: 2.375" (61mm) from mounting surface
Construction:	High impact White ABS plastic case
Connections:	Positive screw terminal connectors
Temperature Range:	0C° - 50°C
Mounting:	Surface-mounted (usually installed near the system amplifier/power supply and other system central equipment).

Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
TOLL-FREE: (800) 666-4800 • Web: www.alphacommunications.com • Email: info@alphacommunications.com

