

# Product data sheet

Specifications



APC NetShelter Basic Rack PDU,  
0U, 1PH, 3.3kW, 100-240V 20A or  
200-240V 16A, 13 C13 outlets,  
C20 inlet

AP6020A

## Overview

<b>Presentation</b>	Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (13) C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
<b>Lead time</b>	Usually in Stock

## Main

<b>Color</b>	Black
<b>Product or Component Type</b>	PDU
<b>PDU Type</b>	Basic
<b>Provided Equipment</b>	Installation guide Safety guide

## Complementary

<b>Input Voltage</b>	100 V 120 V 200 V 208 V 230 V 240 V
<b>Height</b>	15.28 in (38.8 cm)
<b>Width</b>	1.73 in (4.4 cm)
<b>Depth</b>	3.66 in (9.3 cm)
<b>Product Weight</b>	3.3 lb(US) (1.5 kg)
<b>Mounting Location</b>	Front Rear
<b>Mounting preference</b>	Lower
<b>Input Plug Type</b>	IEC 60320 C20
<b>Mounting Mode</b>	Not rack-mountable
<b>Rack units</b>	1U
<b>USB compatible</b>	No
<b>Mounting position</b>	Horizontal
<b>Line Rated Current</b>	16 A
<b>Acceptable Input Voltage</b>	100...240 V
<b>Max line current</b>	20 A
<b>Input current limits</b>	20 A

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Load Capacity	3300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	13 IEC 60320 C13

---

## Environment

---

Product Certifications	cUL Listed CE EAC IRAM PSE UL Listed VDE
------------------------	--

## Ordering and shipping details

---

GTIN	731304327806
------	--------------

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.17 in (43.6 cm)
Package 1 Width	2.99 in (7.6 cm)
Package 1 Length	8.27 in (21 cm)
Package 1 Weight	4.45 lb(US) (2.02 kg)
SCC14	10731304327803

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 38

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

### Energy efficiency

Optimized Energy Efficiency Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

Image of product / Alternate images

Alternative

---

