

# Product data sheet

Specifications



Rack PDU, Basic, Zero U, 14.4kW,  
208V, (24)C13, (4)C19, (2)L6-30R;  
10ft input Cord

AP7599

## Overview

Presentation	Basic Rack PDU 14.4 kW solution for high density installations
Lead time	Usually in Stock

## Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	10 ft (3.05 m)
Number of cables	1
Provided Equipment	Cord retention bracket(s) Documentation CD Installation guide Rack Mounting brackets Toolless Mounting Kit

## Complementary

Input Voltage	208 V 3 phase
Height	70.00 in (177.8 cm)
Width	2.20 in (5.6 cm)
Output Voltage	208 V
Depth	3.74 in (9.5 cm)
Product Weight	21.74 lb(US) (9.86 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Line Rated Current	40 A
Input current limits	50 A
Load Capacity	14400 VA
Input Frequency	50/60 Hz
Number of input connectors	1 CS8365

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Outlet type and quantity</b>	2 NEMA L6-30R 24 IEC 60320 C13 4 IEC 60320 C19
---------------------------------	--

## Environment

---

<b>Product Certifications</b>	cUL Listed CSA METI Denan UL Listed
-------------------------------	--

---

<b>Standards</b>	UL 60950
------------------	----------

---

<b>Ambient air temperature for operation</b>	23...113 °F (-5...45 °C)
--	--------------------------

---

<b>Relative Humidity</b>	5...95 %
--------------------------	----------

---

<b>Operating altitude</b>	0...10000 ft
---------------------------	--------------

---

<b>Ambient Air Temperature for Storage</b>	-13...149 °F (-25...65 °C)
--	----------------------------

---

<b>Storage Relative Humidity</b>	5...95 %
----------------------------------	----------

---

<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)
-------------------------	--

## Ordering and shipping details

---

<b>GTIN</b>	731304240761
-------------	--------------

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	80.98 in (205.7 cm)
-------------------------	---------------------

---

<b>Package 1 Width</b>	12.24 in (31.1 cm)
------------------------	--------------------

---

<b>Package 1 Length</b>	3.11 in (7.9 cm)
-------------------------	------------------

---

<b>Package 1 Weight</b>	30.47 lb(US) (13.82 kg)
-------------------------	-------------------------

## Contractual warranty

---

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

Halogen content performance

Product contains halogen above thresholds

### Energy efficiency

Optimized Energy Efficiency

Energy efficient product

## Use Again

### Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Take-back

Yes

Image of product / Alternate images

**Alternative**

---



