



N3301/AL Aluminum Keypad Module for Access Control



ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The access control keypad(s) shall be Alpha Communications® N3301/AL Keypad Module or approved equal. The N3301/AL shall be installed inside the compatible Nat. Anod. Aluminum Nexa series door panel frames and housings.

The N3301/AL shall support up to 1,000 4,5, or 6 digit access codes, and shall feature a backlit numeric keypad with stainless steel covered push buttons. The unit shall feature a built-in tamper alarm and shall have 2 relay outputs (N/C or N/O) with independent remote activation and a programmable activation time (1 to 99 sec.) and output mode.

Unit shall be powered by a separate 12vac (model# T1240) power supply, or 18vdc to 24vdc power supply.

Contractor shall observe all local and national electrical and building codes.

N3301/AL ALUMINUM KEYPAD MODULE FOR ACCESS CONTROL

The Alpha Communications® N3301/AL Keypad Module is designed to be a stand-alone access control keypad. It is used with the Nexa series Aluminum door panels and modules.

The N3301/AL Keypad Module can handle up to 1,000 4,5, or 6 digit entry codes and features a backlit numeric keypad with stainless steel covered push buttons. Each N3301/AL can be powered by a separate 12vac power supply, or 18vdc to 24vdc power supply.

FEATURES

- Backlit numeric keypad with stainless steel covered push buttons
- Selectable acoustic acknowledgement signal on push
- Light status indication
- Removable terminal connector for easy wiring.
- Built-In Tamper Alarm
- 2 relay outputs (N/C or N/O) with independent remote activation input and panic
- Remote activation inputs can be enabled / disabled through a programmable code
- Programmable activation time (1 to 99 sec.) and output mode
- 1,000 codes of 4, 5 or 6 digits. Each code can be programmed to activate a combination of outputs
- User codes and special codes can be changed without the need to enter into programming mode
- Access control can be disabled during a period of time after the introduction of a number of wrong consecutive codes

DIMENSIONS

O.D. Width: 3.875" (99mm) Height: 4.00" (102mm) Depth: 1.50" (39mm)

NOTE: The dimensions shown are for the N3301/AL module only and do not include any mounting frame and/or housing.

GB2 / IP PLUS SYSTEM INFORMATION

Although the N3301/AL is a stand-alone access control keypad, it can be used in conjunction with the GB2 and/or IP Plus systems and can be mounted into a single panel mounting frame and housing for cosmetic purposes.

