

# HUBBELL

## Premise Wiring

### Non-Metallic Raceway, Non-Metallic PlugTrak Series, PLUGTRAK, 5', 15A 125V, 1-Circuit, Tamper Resistant



By Hubbell Premise Wiring  
Catalog # [PT155112TR](#)

Non-Metallic Raceway, Non-Metallic PlugTrak Series, PLUGTRAK, 5', 15A 125V, 1-Circuit, Tamper Resistant

#### Features

- Available in 5 ft. or 6 ft. lengths
- Multiple spacing configurations
- Hard wired PlugTrak® mates with LANTrak® fittings and boxes

#### General

Catalog Number	PT155112TR
Color	Office White
EU RoHS Indicator	Contact Manufacturer
Item Type	Pre-Wired PlugTrak
Number of Receptacles	5
Performance	Electrical - Crush Resistance - 300 lbs. Electrical - Impact Resistance - 5 ft. lbs Electrical - Receptacle Rating - NEMA 5-15R & 5-20R Environmental - Flame Rating - UL94V-0 Environmental - Temperature Range - -25.6° to 158° F Mechanical - Wire - #12 AWG Stranded Copper
Series	Non-Metallic
Style	Tamper Resistant
Type	Single Circuit
UPC	783585455952

#### Dimensions

Length	5 ft
--------	------

#### Electrical Ratings

Current / Amperage Rating	15 A
Voltage Rating	125 VAC

#### Conductor Related

Wire Size	#12 AWG THHN
-----------	--------------

#### Certifications And Compliance

Industry Standard(s)	CSA Standard C22.2 no. 62 E118895 / E119190 UL Standard UL 5A
----------------------	---

#### Logistics

Carton Quantity	10
-----------------	----

#### Product Assets

- [Catalog Page - PREM U63 CatalogPage](#)
- [Catalog Page - WDK S-62 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Catalogs - Premise Wiring Catalog](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
PREM-PT155112TR-SPEC-EN | REV 6/2024