

Product data sheet

Specifications



APC NetShelter 6U Low-profile Wallmount Rack Enclosure Cabinet 120V Server Depth

AR106V

Overview

Presentation Ideal for retail, healthcare, educational facilities, and light industrial spaces, the low-profile APC wall mount rack offers an efficient solution for deploying hyper-converged servers and networking for edge computing applications. The rack enclosure allows longer depth equipment to be wall-mounted, up to 30 inches deep. A detachable wall bracket and optional casters (sold separately) allow the server rack to be mounted on either the wall or stand alone on the floor. A dust filter and two integrated fans allow deployment in light-industrial environments. Shock packaging is included and allows optional equipment pre-installed before shipment, speeding IT deployment. APC Smart-UPS, APC NetBotz Physical and Environmental Security, and APC EcoStruxure IT can be configured with this cabinet (sold separately). 6U Vertical wall mount cabinet, 30" mounting depth, 250lb weight capacity, 19" rack width, ships fully assembled, MERV 5/G3 dust filter and 120v integrated fans included, input connector IEC 60320 C13, 5 year APC warranty.

Lead time Usually Ships within 2 Weeks

Main

Product or Component Type	Rack enclosure
Main Input Voltage	100 V 120 V
Input Connection Type	IEC 60320 C13
Number of rack unit	6U

Physical

Height	25.51 in (64.8 cm)
Width	13.90 in (35.3 cm)
Depth	38.11 in (96.8 cm)
Product Weight	80.006 lb(US) (36.29 kg)
Color	Black
Mounting Support	Wall
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Mounting position	Vertical
Maximum Mounting Depth	30.00 in (76.2 cm)
minimum mounting depth	30.00 in (76.2 cm)
Rack Width	19"
Permanent permissible load	250 lb(US) (113.4 kg) dynamic 250 lb(US) (113.4 kg) static

Input

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Input Frequency	60 Hz
-----------------	-------

Conformance

Standards	UL 2416 EIA-310E
-----------	---------------------

Environmental

air flow	220 ft ³ /min (103.8 l/s)
----------	--------------------------------------

Ordering and shipping details

GTIN	731304402022
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	16.81 in (42.7 cm)
------------------	--------------------

Package 1 Width	28.90 in (73.4 cm)
-----------------	--------------------

Package 1 Length	41.89 in (106.4 cm)
------------------	---------------------

Package 1 Weight	99.010 lb(US) (44.91 kg)
------------------	--------------------------

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	136
--	-----

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
-----------------------------------	--

REACH Regulation	REACH Declaration
------------------	-----------------------------------

Energy efficiency

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
---------------------	---

Take-back	Yes
-----------	-----

Image of product / Alternate images

Alternative



