TX3 REINFORCED UNIVERSAL SERIES MOUNTING ACCESSORIES

The TX3 Reinforced Universal Series enclosures have several installation options. The reinforced units are equipped for surface mounting. Semi-flush trim kits and gooseneck adapters are available to meet the various installation requirements.

Semi-flush Mounting Trim Kits

TX3-USFTR
Semi-flush Mounting Trim Kit

The TX3-USFTR semi-flush mounting trim kit designed for use with the TX3-2000-4UR Reinforced Universal Series enclosure.

Overall dimensions:
19 5/8" H x 8 7/8" W x 2 1/16" D
(498 mm x 225 mm x 53 mm)

Wall cutout dimensions:
17 1/2" H x 6 1/2" W x 2" D
(445 mm x 165 mm x 51 mm)

TX3-UFTR
Semi-flush Mounting Trim Kit

The TX3-UFTR semi-flush mounting trim kit designed for use with the TX3-2000-8UR Reinforced Universal Series enclosures.

Overall dimensions:
19 ¾" H x 13 ¼" W x 2" D
(502 mm x 336 mm x 51 mm)

Wall cutout dimensions:
17 1/2" H x 10 5/8" W x 2" D
(445 mm x 270 mm x 51 mm)

Gooseneck Adapters

TX3-USGA
Universal Slim Line Gooseneck Adapter

The TX3-USGA Gooseneck mounting adapter is designed for use with the TX3-2000-4UR Reinforced Universal Series enclosure.

TX3-UGA
Universal Gooseneck Adapter

The TX3-UGA Gooseneck mounting adapter is designed for use with the TX3-2000-8UR Reinforced Universal Series enclosures.

Ordering Information

Model	Description
Semi-flush Trim Rings	
TX3-UFTR	Semi-flush mounting kit designed for use with the TX3-2000-8UR Reinforced Universal Series enclosures
TX3-USFTR	Semi-flush mounting kit designed for use with the TX3-2000-4UR Slim Line Reinforced Universal Series enclosure
Gooseneck Adapters	
TX3-UGA	Gooseneck mounting adapter for use with the TX3-2000-8UR Reinforced Universal Series enclosures
TX3-USGA	Gooseneck mounting adapter for use with the TX3-2000-4UR Slim Line Reinforced Universal Series enclosure

Intertek

CATALOG NUMBER **6589**

Rev. 0