

Product data sheet

Specifications



InRow DX 300mm 30kW

ACRD301

⚠ Discontinued on: Apr 24, 2024

⚠ Discontinued - Service only

Overview

Lead time Special Order - Call for Quoted Lead Times

Main

Compressor Type	Scroll
Air flow	3400 ft ³ /min (1604.6 l/s)
Provided Equipment	Installation guide Integrated network management Network Management Card Optional concrete pad User Manual

Physical

Height	78.4 in (199.1 cm)
Width	11.8 in (30 cm)
Depth	43.1 in (109.5 cm)
Net Weight	352.70 lb(US) (159.98 kg)

Input

Input power 850 W

Environmental

Ambient Air Temperature for Operation	-13...104 °F (-25...40 °C)
Ambient Air Temperature for Storage	-4...122 °F (-20...50 °C)
Operating altitude	0...10000 ft
acoustic level	77.1 dBA

Communications & Management

Control panel Multi-function LCD status and control console

Accuracy

Air Discharge Patterns Horizontal

Ordering and shipping details

GTIN 731304344773

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.7 in (215.2 cm)
Package 1 Width	44.8 in (113.7 cm)
Package 1 Length	26.02 in (66.1 cm)
Package 1 Weight	440.90 lb(US) (199.99 kg)

Contractual warranty


Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---


Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.
