Important Note

Power strips used within the patient care vicinity may be permanently attached so that it is only removable with a tool. Choose the PSCLAMP for a safe and secure mounting solution.

Safe-IT UL 60601-1 Medical-Grade Surge Protector for Patient-Care Vicinity, 4x Hospital-Grade Outlets, 6 ft. Cord, Antimicrobial Protection

MODEL NUMBER: **SPS406HGULTRA**








Full 60601-1 compliance and agency listing, surge protection, integrated locking safety covers and a 6 ft. cord make this medical-grade power strip ideal for standalone use in areas inside and outside patient-care vicinities.

Features

Power Distribution Anywhere in Any Medical Facility Ideal for standalone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas120V, 50/60 Hz power strip complies with UL 60601-1 and UL 60950-1 specificationsAutomatic single-fault protectionTested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 Canadian standardsPatent # 7,375,939 & 8,339,759

Exclusive Antimicrobial Protection Antimicrobial coating helps resist the growth of bacteria, viruses, fungi, mold and mildewCoating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products

Versatile Medical-Grade Solution4 NEMA 5-15R-HG hospital-grade outlets provide consistent power6 ft. power cord with NEMA 5-15P-HG plug provides ample reach to the power sourceRugged all-metal housing for long life in demanding environments

Premium Safety Features1410 joules of surge suppression protect against dangerous power spikesIntegrated locking outlet safety covers block access to unused outletsBuilt-in 15A resettable circuit breaker protects against dangerous overloadsSwitchless design prevents accidental shut-offLED indicates power is present and surge-protected

Ready to Use Right Out of the Box Built-in mounting slots and flanges for easy installation on a variety of surfaces

Highlights

- Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew
- Approved for standalone use in all patient-care vicinities
- Listed to UL 60601-1 and UL 60950-1 specifications
- 1410 joules of surge suppression
- Automatic single-fault detection for added patient protection

Package Includes

- SPS406HGULTRA UL 60601-1 Medical-Grade Power Strip
- Owner’s manual

Specifications

OVERVIEW	
UPC Code	037332194091
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A 120V
Voltage Compatibility (VAC)	120
Maximum Surge Amps	60000
Input Plug Type	NEMA 5-15P-HG
Input Cord Length (ft.)	6
Right-Angle Plug	No
Input Cord Length (m)	1.83
Integrated Cord Clip	No
OUTPUT	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(4) 5-15R-HG
Circuit Breaker (amps)	15
Overload Protection	15A resettable circuit breaker
Outlet Orientation	Single row of 4
Right-Angle Outlets	No
USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED(s)	Yes
LED Indicators	Proper wiring and surge protection working
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	1410
Automatic Shut-Off	No
DATALINE SURGE SUPPRESSION	
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Telephone/DSL Protection	No

PHYSICAL	
Material of Construction	Metal
Power Cord Color	White
Housing Color	White
Mounting Holes or Slots	Yes
Receptacle Color	White
Shipping Dimensions (hwd / in.)	2.40 x 5.80 x 14.40
Shipping Dimensions (hwd / cm)	6.10 x 14.73 x 36.58
Shipping Weight (lbs.)	2.60
Shipping Weight (kg)	1.18
Unit Dimensions (hwd / in.)	1.500 x 13.750 x 2.500
Unit Dimensions (hwd / cm)	3.8 x 34.9 x 6.4
Unit Weight (lbs.)	3.20
Unit Weight (kg)	1.45
Mounting Details	Includes flanges
FEATURES & SPECIFICATIONS	
Rotatable Outlets	No
Antimicrobial	Yes
Mounting Accessory Included	Yes
Antibacterial	No
STANDARDS & COMPLIANCE	
Patented	Patent# 7,375,939; Patent# 8,339,759
Product Certifications	CAN/CSA-C22.2 No. 601.1; CAN/CSA-C22.2 No. 601.1-M90 (Canada); CAN/CSA-C22.2 No. 60950-1 (Canada); UL 60950-1; UL 60601-1
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.