

Product data sheet

Specifications



Maintenance Bypass Panel, single unit, 150kW 400V wallmount, for Galaxy VS and Easy UPS 3M

GVSBPSU150KH

Overview

Presentation	Maintenance bypass cabinet for complete isolation of the UPS during service operations.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	400 V 3 phase
Product or Component Type	Panel
Range of Product	Galaxy VS
Range Compatibility	Galaxy VS

Physical

Height	31.5 in (80 cm)
Width	23.6 in (60 cm)
Depth	11.02 in (28 cm)
Net Weight	105.8 lb(US) (48 kg)

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...3000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN	731304405658
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.3 in (49 cm)
Package 1 Width	33.07 in (84 cm)
Package 1 Length	48.03 in (122 cm)
Package 1 Weight	132.3 lb(US) (60 kg)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)