

Product datasheet

Specifications

APC IT Power Distribution Module 3 Pole 5 Wire 16A IEC309 380cm



PDM3516IEC-380

Overview

Presentation Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

Lead time Usually Ships within 3 Weeks

Main

Main Input Voltage 400 V 3 phases

Main Output Voltage 230 V
400 V 3 phases

Provided equipment Installation guide

Physical

Colour Grey

Height 15.2 cm

Width 43.2 cm

Depth 40.6 cm

Net weight 2.19 kg

Input

Network frequency 50 Hz

Max line current 16 A

Output

Max current draw 16 A

Number of power socket outlets 1 IEC 309 16 A

Conformance

product certifications CE
VDE

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 15.2 cm

Package 1 Width 40.6 cm

Package 1 Length	43.2 cm
------------------	---------

Package 1 Weight	3.1 kg
------------------	--------

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performances. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Take-back Transparency

Resource performance

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Under investigation

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)

Image of product / Alternate images

Alternative





