



Product: [FRMT5K](#)

Fiber Raceway Mounting Trapeze Style Kit, 300mm



Product Description

Fiber Raceway Mounting Trapeze Style Kit, 300mm

Technical Specifications

Product Overview

Environmental Space:	Indoor
----------------------	--------

Construction

Weight:	2.094 lbs
Overall Height:	1.259 in (31.979 mm)
Overall Width:	1.968 in
Overall Length:	12.992 in

Product Material

Materials

Material
Mild steel Extensions: Nickel Plated finish Duct Bracket: Powder coat Black Threaded rod, nuts & washers: zinc plated finish

Related Part Numbers

Variants

Item #	Color	Length
FRMT5K	Metallic	12.992 in

Product Notes

Notes:	The mounting bracket kit is used to attach (300x100mm) plastic duct to duct mounting ironwork. They allow 300mm ducting to be fitted to either 1/2" or 5/8" UNC threaded rods, or alternatively M12 and M16 metric threaded rods. This kit consists of: a 300mm duct mounting bracket with 3 x M12 hex head set screws and nuts and 2 x straight brackets. The mounting bracket grips the 300mm ducting and bolts to the supporting brackets. The straight bracket/s are secured onto either 1/2" or 5/8" UNC threaded rods, or alternatively M12 and M16 metric threaded rods; which are supplied with kits. These kits are both available separately. Typically, the 1/2" dia UNC threaded rods (alternatively M12 threaded rods) are used for suspended mounting from the ceiling; whilst the 5/8" dia UNC threaded rods (alternatively M16 threaded rods) are used for mounting the duct system above racks.
--------	--

History

Update and Revision:	Revision Number: 0.170 Revision Date: 03-28-2024
----------------------	--

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.