Specifications

Eaton EBA200-10



Catalog Number: EBA200-10

Eaton Basic rack PDU, 0U, L14-30P input, 5.76 kW max, 120/240V, 24A, 10 ft cord, Split-phase, TAA compliant, Outlets: (8) 5-20R, (20) C13 Outlet grip, (6) C19 Outlet grip

General specifications

Product Name	**Catalog Number**
Eaton basic PDU	EBA200-10
UPC	**Product Length/Depth**
786685974699	66.5 in
Product Height	**Product Width**
2.09 in	2.05 in
Product Weight	**Warranty**
11.5 lb	3 year
Compliances	**Certifications**
TAA Compliant	UL Listed

Powering Business Worldwide

Product specifications

Form factor
0U (Vertical)

Outlet control
No

Phase
Split-phase

Wattage
5.76 kW max

Amperage Rating
24A

Input voltage
120/240V

Input connection
L14-30P

Outlets
(8) 5-20R, (20) C13 Outlet grip, (6) C19 Outlet grip

Cord length
10 ft

Frequency rating
50-60 Hz

Ethernet interface
No

Serial interface
No

Operating Temperature
0° to 60°C (32° to 140°F)

Resources

Certification reports
Eaton RoHS declaration of conformity: ePDU G3

Eaton RoHS Declaration of Conformity: ePDU G3

Drawings
Eaton ePDU EBA200-10 technical drawing

Installation instructions
Eaton ePDU G3 troubleshooting guide

Manuals and user guides
Eaton ePDU G3 operations manual

Eaton ePDU G3 replace and configure eNMC module

Eaton ePDU G3 1U and 2U installation addendum

Eaton ePDU G3 installation and connectivity quick start

Specifications and datasheets
Eaton Specification Sheet - EBA200-10



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia