

# Product data sheet

Specifications



## APC NetShelter SX, Server Rack Enclosure, 12U, Shock Packaging, Black, 658H x 600W x 900D mm [TAA]

AR3003SP

### Overview

**Presentation** An industry-standard rack with the most standard features for speed of deployment and installation. Ready for low to medium density edge computing. Shorter height allows for deployment underneath cabinets, desks, in remote office branch office spaces for a secure and discrete solution for IT devices.

**Lead time** Usually in Stock

### Main

<b>Product or Component Type</b>	Rack enclosure
<b>Number of rack unit</b>	12U
<b>Provided equipment</b>	Casters Communication Cable Door Key(s) Leveling feet Pallet ramps Reusable packaging Roof Side Panels

### Physical

<b>Height</b>	25.91 in (65.8 cm)
<b>Width</b>	23.62 in (60 cm)
<b>Depth</b>	35.43 in (90 cm)
<b>Product Weight</b>	119.006 lb(US) (53.98 kg)
<b>Color</b>	Black
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Not rack-mountable
<b>Maximum Mounting Depth</b>	29.75 in (75.57 cm)
<b>minimum mounting depth</b>	7.52 in (19.1 cm)
<b>Rack Width</b>	19"
<b>Marking</b>	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
<b>Permanent permissible load</b>	600 lb(US) (272.2 kg) dynamic 600 lb(US) (272.2 kg) static

### Conformance

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Standards</b>	UL 2416 UL 60950-1 EIA-310E
------------------	-----------------------------------

## Ordering and shipping details

---

<b>GTIN</b>	731304347644
-------------	--------------

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	37.80 in (96 cm)
<b>Package 1 Width</b>	42.13 in (107 cm)
<b>Package 1 Length</b>	29.53 in (75 cm)
<b>Package 1 Weight</b>	238.10 lb(US) (108 kg)

## Compliance

---

<b>Compliance</b>	TAA BAA via COTS
-------------------	---------------------

## Contractual warranty

---

<b>Warranty</b>	5 year repair or replace
-----------------	--------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	328
--	-----

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
-----------------------------------	--

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

### Energy efficiency

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

## Use Again

### Repack and remanufacture

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

Take-back	Yes
-----------	-----

Image of product / Alternate images

Alternative

---

