

3/4" & 1" Steel Door Recessed Switch Set

WWW.GRISK.COM



180 / 184 / 8080-T Series



◆ Recessed magnetic contact

◆ 12" #22AWG leads or screw terminals

◆ Longer leads, zip cord or jacketed cable upon request

◆ Built in E.O.L. Resistors and Diodes upon request

◆ Supervisory Loops upon request

◆ Colors white, brown, gray, black

◆  Indicates U.L. 10C Fire Rated



180-12



184-12 C€



8484-T



8080-T

Part Numbers

		<u>Closed Loop</u>	<u>Open Loop</u>	<u>SPDT</u>	<u>DPDT</u>
Standard Gap up to 1/2" on steel*	3/4" Dia.	180-12 	185-12	190-12	195-12
	1" Dia.	C€ {184-12} 	189-12	194-12	C€ {199-12}
	3/4" Dia	8080-T	8585-T		
	1" Dia.	8484-T	8989-T		
Wide Gap 3/4"+ on steel*	3/4" Dia.	180-12WG 	185-12WG	190-12WG	195-12WG
	1" Dia.	184-12WG 	189-12WG	194-12WG	199-12WG
	3/4" Dia	8080-TWG	8585-TWG		
	1" Dia.	8484-TWG	8989-TWG		

7/8" Diameter also available. P/N 81-12 & 81-12WG, white or black only. Call the factory for more information.

INSTALLATION APPLICATIONS

The GRI 180-12 is the industry standard 3/4" diameter recessed steel door switch set with 12" leads. The innovative GRI 8080-T series is a 3/4" diameter recessed switch set designed for residential, commercial and industrial doors and frames. The shorter length terminals makes the installation of the set quick and simple.

WARRANTY: Lifetime warranty against workmanship, material and factory defects.

GEORGE RISK INDUSTRIES, INC.
G.R.I. PLAZA
KIMBALL, NE 69145

WWW.GRISK.COM



1-800-445-5218
1-800-523-1227
(308) 235-4645
FAX (308) 235-3561
E-MAIL: sales@grisk.com