# UK Computer Power Cord - BS1363 to C5, 2.5A, 250V, 18 AWG, 6 ft. (1.83 m), Black

MODEL NUMBER: **P060-006**









UK computer power cord connects your computer or peripheral with a C6 inlet to any grounded AC power outlet that accepts BS1363 plugs.

### Features

**UK Plug to C5 Power Cord Connects Notebook Computers to a BS1363 AC Outlet**This UK computer power cable is designed for connecting a notebook computer, laptop or other device with a three-slot C6 inlet to a UPS system, PDU or other BS1363 outlet. It is also a durable replacement for a worn-out or lost laptop power cord. The 6-ft. (1.83 m) length allows you flexibility in placing equipment with respect to the power outlet.

### Highlights

- UK computer power cable for powering notebooks and laptops with C6 inlets
- 6-ft. (1.83 m) length allows flexibility in placing devices in relationship to AC outlet
- Ideal replacement for worn-out or missing UK IEC power cord

### Applications

- Connect a laptop or notebook computer to a PDU up to 6 ft. (1.8 m) away in your workstation
- Extend an existing power connection up to 6 ft. (1.8 m) to more easily place a device or reach a power source
- Provide a high-quality replacement for a worn-out or missing power cord

### Package Includes

- P060-006 BS1363 to C5 UK Computer Power Cable, 6 ft. (1.8 m), Black

## Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332153630 |
| Device Compatibility | Laptop; Computer; UPS; PDU |
| Country/Region | UK |
| **INPUT** | |
| Maximum Input Amps | 2 |
| Voltage Compatibility (VAC) | 100-250 |
| **CONNECTIONS** | |
| Side A - Connector 1 | BS1363 UK PLUG |
| Side B - Connector 1 | IEC-320-C5 |
| **PHYSICAL** | |

| | |
|---|---|
| Plug Color | Black |
| Cable Jacket Color | Black |
| Cable Jacket Material | PVC |
| Power Cord Jacket Type | H05VV-F |
| Cable Outer Diameter (OD) | 6.5mm |
| Number of Conductors | 3 |
| Wire Gauge (AWG) | 18 |
| Wire Gauge (OD - mm²) | 0.82 |
| Cable Length (ft.) | 6 |
| Cable Length (m) | 1.83 |
| Shipping Dimensions (hwd / in.) | 9.06 x 7.09 x 0.50 |
| Shipping Dimensions (hwd / cm) | 23.01 x 18.01 x 1.27 |
| Shipping Weight (lbs.) | 0.46 |
| Shipping Weight (kg) | 0.21 |
| Unit Dimensions (hwd / in.) | 9.060 x 7.090 x 0.500 |
| **ENVIRONMENTAL** | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range | 20% to 70% RH |
| Storage Humidity Range | 20% to 80% RH |
| **FEATURES & SPECIFICATIONS** | |
| Antibacterial | No |
| Angled Plug | No |
| High Voltage | Yes |
| Locking Plug | No |
| Coiled Power Cord | No |
| **STANDARDS & COMPLIANCE** | |
| Product Certifications | UL Listed; cUL Listed |
| Product Compliance | CE (Europe); REACH; RoHS; UKCA |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.