

Product data sheet

Specifications

APC IT Power Distribution Module 3 Pole 4 Wire 50A CS50 260cm



PDM3450CS50-260

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phase
Main Output Voltage	208 V 3 phase
Output connector type	CS50 1
Provided Equipment	Installation guide

Physical

Color	Black
Height	5.0000000000 in (12.7 cm)
Width	17.5 in (44.5 cm)
Depth	16.0 in (40.6 cm)
Net Weight	8.62 lb(US) (3.91 kg)

Input

Input Frequency	60 Hz
Permissible voltage	200...240 V
Max line current	50 A

Output

Maximum Total Current Draw per Phase	50 A
Number of power socket outlets	1 CS50

Conformance

Product Certifications	UL Listed
-------------------------------	-----------

Ordering and shipping details

GTIN	731304281511
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0000000000 in (12.7 cm)
Package 1 Width	16.0 in (40.6 cm)
Package 1 Length	17.5 in (44.5 cm)
Package 1 Weight	9.81 lb(US) (4.45 kg)

Contractual warranty

Warranty	1 year repair or replace
-----------------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Take-back Transparency

Resource performance

Take-Back Program Available

Well-being performance

Mercury Free

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Under investigation

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)
